


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Seward</u>	$\frac{1}{4}$ C $\frac{1}{4}$ NW $\frac{1}{4}$	34	T 31 S	R 31 EW

Distance and direction from nearest town or city street address of well if located within city?

From Plains: 6 W, 2½ N and E into--

2 WATER WELL OWNER:	H-30 Drilling	H-30 Permitted-
RR#, St. Address, Box # :	251 N Water, #10	Board of Agriculture, Division of Water Resources
City, State, ZIP Code :	Wichita, KS 67202	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 300 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 210 ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 210 ft. below land surface measured on mo/day/yr 11-30-89
	Pump test data: Well water was 220 ft. after 1 hours pumping 95 gpm
	Est. Yield 95 gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 9½ in. to 300 ft., and in. to ft.
	WELL WATER TO BE USED AS:
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
	Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter 5 in. to 300 ft., Dia			11 Other (specify)
Casing height above land surface 24 in., weight			12 None used (open hole)
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC		
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 200 ft. to 300 ft.		
GRAVEL PACK INTERVALS:	From 20 ft. to 300 ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other dirt
Grout Intervals:	From 1 ft. to 20 ft.			
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? West			13 Insecticide storage	
			How many feet? 200	

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	4	Top soil			
4	64	Tan Clay			
64	77	Fine and Medium Sand			
77	89	Tan Sandy Clay			
89	137	Fine and Medium Sand			
137	177	Lt. Brown Sandy Clay			
177	198	Fine and Medium Sand			
198	208	Yellow Clay and Gravel			
208	232	Sandy Gravel			
232	255	Yellow Clay			
255	267	Sand and Medium Sand			
267	300	Yellow and White Clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-30-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. KWWCL-430 This Water Well Record was completed on (mo/day/yr) 11-30-89 under the business name of Howard Drlg. Co. Box 806 Beaver, OK 73932 by (signature) [Signature]
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.