USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215



Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| | County | Fraction | | Section | number | Township number | Range number | |
|-----------------------------------------------------------------------------------------|-------------------------------------|---------------------------|-----|---------|------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------|-----------------------------------|-------------------------------|
| 1. Location of well: | Seward | NW 1/4 NW 1/4 SB | 1/4 | 20 |) | T 31 S | R 32 EΔW | |
| Distance and direction from nearest town or city: 12F. Plans 3. Owner of R.R. or stree | | | | | | aron Mills Hutchinson Nat | ional Bank | |
| Ct. at address of well leasting if in aircuit | | | | | te, zip code: Dodge City, Kansas 6. Bore hole dia. 28 in. Completion date 6-26-76 | | | |
| 4. Locate with "X" in section below: Sketch map: | | | | | Do | 6. Bore hole dia. 28 in. Well depth 434 ft. | Completion date 6-26- | 76 |
| NW corner of the SE ₄ , Sec. 20 T31S, R32W, Seward Co., Kans. | | | | | | 7 Cable tool Rotary | Driven Dug Bored X Reverse rotary | |
| E - SW SE | | | | | | 8. Use: Domestic Public supply Industry | | |
| | | | | | | | | |
| S 1 Mile | | | | | | RMP PVC Dia. 16 _{in.} to 193 _{t.} dept | _iWeightIbs./ft. | |
| 5. Type and color of material | | | | From | То | Diain. toft. depth gage No219 10. Screen: Manufacturer's name Doerr, Foster Type Louver, Millslot 16" | | |
| Top soil | | | | 0 | 2 | | | |
| Tan clay | | | | 2 | 62 | Slot/gauze 1/8" Set between 193 | Length 241 | |
| Sandy tan clay | | | | 62 | 82 | Gravel pack? X Size ran | | |
| Fine to coarse sand | | | | 82 | 178 | 11. Static water level: 196 ft. below land surf | ace Date 4-14-76 | |
| Coarse sand and fine gravel | | | | 178 | 358 | 12. Pumping level below land 208 ft. after 3 h | surfaces: | |
| Hard streaks caliche | | | | 358 | 360 | 212 ft. after 1 h | rs. pumping <u>2005</u> g.p.m. | |
| Coarse to medium gravel | | | | 360 | 434 | 13. Water sample submitted: | mo./day/yr. | |
| Tan and white clay | | | | 434 | 460 | 14. Well head completion: | Date | |
| | | | | | Pitless adapter X 15. Well grouted? Yes | | | |
| | | | | | With: Neat cement X Depth: From Off. to | Bentonite Concrete | - W | |
| | | | | | | 16. Nearest source of possible ft Direction | contamination: | / |
| | | | | | | Well disinfected upon comple | | ks. |
| | | | | | | 17. Pump: Manufacturer's name La | yne & Bowler | $\mathcal{O}_{ \mathcal{N} }$ |
| | | | | | | Length of drop pipe 280 | HP 200 g.p.m. | (3) |
| | | | | | | Type: Submersible | X Turbine | A. |
| (Use a second sheet if needed) | | | | | | Jet Centrifugal | Reciprocating Other | \$ 10 \\ |
| 18. Elevation: | 19. Remarks: | | | | | 20. Water well contractor's c This well was drilled under my | | 7 |
| Topography: | | | | | | is true to the best of my know Layne-Western | Co., Inc. 102 | 312 |
| Hill Slope | | | | | | Address Garden | License No. | 312 |
| Upland Valley | | | | | | Signed Authorized repr | esentative / Dec 76 | 2 S |
| Forward the white, blu | e and pink copies to the Department | of Health and Environment | | | | | Form WWC-5 | 'η |