

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

County Seward		Fraction SE 1/4 SE 1/4 SW 1/4		Section number 26		Township number T 31 S		Range number R 32 E	
1. Location of well: 4 miles W of Kismet, Kansas Street address of well location if in city:				3. Owner of well: Warren Angell R.R. or street: City, state, zip code: Plains, Kansas 67869					
4. Locate with "X" in section below: <div style="display: flex; align-items: center;"><div style="text-align: center;"><div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;">N</div><div style="display: flex; justify-content: space-around; width: 100px;"><div style="border: 1px solid black; padding: 5px;">NW</div><div style="border: 1px solid black; padding: 5px;">NE</div></div><div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;">W</div><div style="display: flex; justify-content: space-around; width: 100px;"><div style="border: 1px solid black; padding: 5px;">SW</div><div style="border: 1px solid black; padding: 5px; text-align: center;">X</div><div style="border: 1px solid black; padding: 5px;">SE</div></div><div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;">S</div><div style="display: flex; justify-content: space-around; width: 100px;"><div style="border: 1px solid black; padding: 5px;">1 Mile</div><div style="border: 1px solid black; padding: 5px;">1 Mile</div></div></div><div style="margin-left: 20px;">SE corner of the SW₄, Sec.26, T31S, R32W, Seward Co., Kansas</div></div>				Sketch map:		6. Bore hole dia. 28 in. Completion date 5-7-76 Well depth 528 ft.			
5. Type and color of material				From		To		7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary	
								8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other	
								9. Casing: Material STL Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 37 lbs./ft. Dia. 16 in. to 226 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. 219	
								10. Screen: Manufacturer's name Doerr and Poster Louwer and Dia. 16 " Type Millislot Slot/gauze 1/8 " Length 302 " Set between 226 ft. and 528 ft. Gravel pack? yes Size range of material 3.1-7.5mm	
								11. Static water level: <input type="checkbox"/> mo./day/yr. 206 ft. below land surface Date 12-15-75	
								12. Pumping level below land surfaces: 218 ft. after 1 hrs. pumping 1040 g.p.m. 250 ft. after 1 hrs. pumping 2100 g.p.m. Estimated maximum yield 2400 g.p.m.	
								13. Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date <input type="checkbox"/>	
								14. Well head completion: <input type="checkbox"/> Pitless adapter <input checked="" type="checkbox"/> <input type="checkbox"/> Inches above grade	
								15. Well grouted? yes With: <input type="checkbox"/> Neat cement <input checked="" type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.	
								16. Nearest source of possible contamination: Unk ft. <input type="checkbox"/> Direction <input type="checkbox"/> Type <input type="checkbox"/> Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
17. Pump: <input type="checkbox"/> Not installed Manufacturer's name Layne & Bowler Model number 12TH HP 200 Volts <input type="checkbox"/> Length of drop pipe 300 ft. capacity 2000 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other									
18. Elevation: Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley				19. Remarks: (Use a second sheet if needed)		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Layne - Western Co. 150 Business name License No. Address Garden City, Kansas Signed R. J. Vincent Date 5-24-76 Authorized representative			

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5

TEST HOLE REPORT

Layne-Western Company, Inc.



WATER SUPPLY SERVICES SINCE 1924

TEST DRILLING • WATER WELLS • PUMPS

Contract Name Warren Angell

Job No. K-543

Date 9-9-75

City Plains

State Kansas

Driller McIntyre

Location of Test Hole SE corner of

Elevation of Test Hole _____

Static Water Level 206'

Measured in well _____ Hours After Completion

1/4 SW 1/4 Sec. 26 of T 31S
R 32W, Seward Co., Kansas

From	To	Description of Strata	Water Bearing	
0	3	Top soil		
3	90	Fine sand clay streaks		
90	195	Fine to coarse sand		
195	227	Yellow clay		
227	250	Fine to coarse sand		
250	265	Blue clay		
265	275	Fine to coarse sand		
275	290	Blue clay		
290	295	Fine to coarse sand		
295	305	Blue clay		
305	370	Fine co medium sand		
370	390	Fine to coarse sand fine gravel		
390	422	Tan sandy clay		
422	462	Tan sandy clay sand lenses		
462	470	Fine to coarse sand		
470	480	Tan sandy clay		
480	528	Fine to coarse sand yellow chalk and clay streaks		
528	540	Red bed		

Remarks:

Well site