			WAT	ER WELL RECORD					
	ON OF WA		Fraction		Sec	ction Number	Township Number	Range Number	
County:	Sevard		SE		NE 1/4	28	T 31 S	R 32 E/W	
			-	address of well if lo		1	•• • • • • •	1	
			h of Lib	eral 4 Nor			West into		
_	R WELL OW		thodic D	ioceses 1-		gn Opera	_		
	RR#, St. Address, Box # : 621 17 th Streetoard of Agriculture, Division of Water Resources								
	, ZIP Code	<u> </u>	1-1				Application Number:		
3 LOCATI	E WELL'S L IN SECTION	OCATION WITH							
AIV A	IN SECTION	N BOX:						3	
ī		1						r 12-12-90	
	NW	NE	Pur	np test data: Well	water was . 20	0 ft. aft	ter2 hours p	oumping 80 gpm	
1 [1444	1,46	Est. Yield	.90 gpm: Well	water was	ft. aft	ter hours p	oumping gpm	
ي <u></u> ل	i	•	Bore Hole Dian	neter 9 in.	. _{to} . 340		nd	in. to	
* w -	_	,	WELL WATER	TO BE USED AS:	5 Public water	er supply 8	3 Air conditioning 1	1 Injection well	
7	544	1	1 Domesti	c 3 Feedlot	6 Oil field wa	ter supply	9 Dewatering 12	2 Other (Specify below)	
	2W	36	2 Irrigation	4 Industrial	7 Lawn and	garden only 1	0 Monitoring well		
1 1	i		Was a chemica	l/bacteriological sam	ple submitted to D	epartment? Ye	s, If ye	es, mo/day/yr sample was sub-	
<u> </u>		5	mitted			Wate	er Well Disinfected? Yes	X No	
5 TYPE (OF BLANK (CASING USED:		5 Wrought iron	8 Concr	ete tile	CASING JOINTS: Glu	ed X Clamped	
	eel	3 RMP (S	SR)	6 Asbestos-Cem	ent 9 Other	(specify below)) We	lded	
2 P\	/C	4_ABS		7 Fiberglass		<i>.</i>	Thr	eaded	
Blank casi	ing diameter	. 5	.in. to 3.4	0 ft., Dia	in. to	· ·		. in. to ft.	
Casing he	ight above la	and surface	14	in., weight	200	Ibs./ft	t. Wall thickness or gauge	No. 0.265	
TYPE OF	SCREEN O	R PERFORATIO	N MATERIAL:		7 PV	/C	10 Asbestos-cen	nent	
1 St	eel	3 Stainles	s steel	5 Fiberglass	8 RM	MP (SR)	11 Other (specif	y)	
2 Br	ass	4 Galvania	zed steel	6 Concrete tile	9 AE	BS	12 None used (d	open hole)	
SCREEN	OR PERFO	RATION OPENIN	IGS ARE:	5 G	auzed wrapped	_	8 Saw cut	11 None (open hole)	
1 Cc	ontinuous slo	ot 3 M	fill slot	6 W	Vire wrapped	_	9 Drilled holes		
2 Lo	uvered shut	ter 4 K	(ey punched	7 T	orch cut		10 Other (specify)		
SCREEN-	PERFORAT	ED INTERVALS:	From	240 ft. f	o 340	ft., From	1 ft.	toft.	
								toft.	
(GRAVEL PA	CK INTERVALS:	: From	2.20 ft. f	340	ft., From	1 ft.	toft.	
			From		to			to ft.	
6 GROUT	T MATERIAL	.: 1 Neat	cement	12.004			Other Hole Plug		
_				_	ft.	to	ft., From	ft. to ft.	
What is th	e nearest so	ource of possible	contamination:			10 Livesto	ock pens 14	Abandoned water well	
1 Septic tank 4 Lateral lines			ral lines	7 Pit privy		11 Fuel storage		Oil well/Gas well	
2 Sewer lines 5 Cess pool				8 Sewage lagoon				Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage									
Direction f	-	Southwe		•		How man	y feet? 250		
FROM	TO		LITHOLOGIC	CLOG	FROM	TO	PLUGGING	INTERVALS	
0	225	Overburd	len						
225	240	Medium s	sand						
240	260	Medium s	and						
260	280	Medium s							
280	300	Medium s							
300	320	Medium s							
320	340	Medium s					77		
								MEA.11.	
7 CONT	PACTORIS (B'S CEDTIEICA	TION: This water	all was (1) constru	icted (2) roos	netructed or (3) plugged in	nder my jurisdiction and was	
								noer my jurisdiction and was incoming the my jurisdiction and was incoming the manual	
•		/year) 's License No. .		This Wate			10 00		
l	II CONTRACTOR	S LICERSE NO		inis wat	ei vveli necora Wa	as completed o	n (mo/u py (yr) _y .÷∻∻		
							ma) (\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		
	business na		W Water	Well Servi	ce, Inc.	by (signati	the correct answers. Send top thre	selle	