WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

3 1	County	Fraction	Section	n number	Township number	Range number
1. Location of well:	Seward	SW 1/4 SW 1/4 NW 1/4		2-	T 31 S	R 33 ≣∕ W
2. Distance and dire	ction from nearest town or city:	7 S., 1 W., R.	Owner of w		ndall Bird	
Street address of well	location if in city: 1/2 N . C	of Sublette, Ks ci	R. or street: ty, state, zi	RFI code:) <u>Sublett</u> e. Kans	.ac 67877
4. Locate with "X" i	in section below:	Sketch map:			6. Bore hole dia. 28 in. Well depth 405 ft.	
N	· · · · · · · · · · · · · · · · · · ·					
E W					7 Cable tool X Rotary Hollow rod Jetted	Driven Dug Bored Reverse rotary
					8. Use: Domestic Public supply Industry XX Irrigation Air conditioning Stock Lawn Oil field water Other	
SW	SE				9. Casing: Material STL	_ Height: Above or below
					Threaded WeldedXX	
. <u>.</u> 1 M					Dia.15 in. to405 ft. dep	th Wall Thickness: inches or
5. Type and color of material				То	Dia in. to ft. dept	
700	and fine cond		r	90	L.B. Foster	
Top soil and fine sand					Type Millslot Slot/gauze 125	Length
Fine sand and clay				120	Set between 175	ft. and <u>405</u> ft.
Coarse sand and fine gravel				150	Gravel pack? YBS Size ra	nge of material 1/2 DOWN
п			150	180	11. Static water level:	mo./day/yr.
Coseco c	and fine eravel	and clay etroak	. 18I	210	12, Pumping level below land	i surfaces:
Coasse sand, fine gravel, and clay streaks					ft. after 24	nrs. pumping g.p.m.
Coarse sand and fine gravel				240	Estimated maximum yield	
Coarse sand				270	13. Water sample submitted: Yes XX No	mo./day/yr. Date
Mod. sand and clay streaks				300	14. Well head completion:	
Coarse sand and play streaks				3 8 0	Pitless adapter	12 Inches above grade
Coarse sand and fine gravel				360	15. Well grouted? <u>VBS</u> With:Neat_cement X	Bentonite Concrete
				<u> </u>		
Coarse sand and graveel				390	16. Nearest source of possible ft. NODE Direction	Туре
Sand and gravel (390–415) Clay and Rock				420	Well disinfected upon comple	
Clay and rock						Not installed orthington
					Model number 15m 185 Length of drop pipe 300	HP <u>160</u> Volts ft. capacity 1800, p.m.
				+	Length of drop pipe Type:	
### · · · · · · · · · · · · · · · · · ·				- 	Submersible	XX Turbine Reciprocating
	(Use a second :	heet if needed)			Gentrifugal	Other
18. Elevation:	19. Remarks:				20. Water well contractor's of This well was drilled under m	
					is true to the best of my know	' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' '
Topography: Hill					Clemens Irr.	Orlg. 33fl License No.
Slope					Address P. D. D.	9 Liberal
XX Upland Valley					Signed Authorized rep	resentative Date
	ue and pink copies to the Department	of Health and Environment				Form WWC-5