		WWC-5		sion of Water		Well ID				
Original Record		ge in Well Use		urces App. No.	Township Numb		ner			
1 LOCATION OF W County: 24	ATER WELL:	1 1/2 /W 1/2 SW	1/4 SW1/4 SECT	ilon-sulliber	T 3/ S	R T DE				
2 WELL OWNER: I	net Name: []	First: Belly		al Address who		(if unknown, distance as	T			
2 WELL OWNER: L. Business: Box 65	asi walle. Young	לוושט ווואני				r's address, check here				
Address.			1							
Address: Satante	State: K	S ZIP: 67870	19 Mile	y North	4 Miles G	vort of Liber	6/			
3 LOCATE WELL	State.	Zii. V i Gi								
WITH "X" IN	4 DEPTH OF COM	APLETED WELL	: .) 7 ft.			(decimal de	-			
SECTION BOX: Depth(s) Groundwater Encountered: 1) 2)			It.	ft. Longitude:			egrees)			
well's static water level:21										
□ below land surface, measured on (mo-da				GPS (unit make/model:)						
above land surface, measured on (mo-da			yr) (WAAS enabled? \(\subseteq \text{ Yes} \subseteq \text{No} \)		,					
Pump test data: Well water was										
E E	I .	s pumping water was	_		ne Mapper:		• • • • • • • • • • • • • • • • • • • •			
- SW SE	after hour	s numning								
Estimated Yield:gpm			6 Elevation:ft. Ground Level 1							
S	Bore Hole Diameter:	7 in. to					•			
mile		in. to	ft.		J Other					
7 WELL WATER TO 1. Domestic:		oton Cumulus, wall ID		10 🗆 🔾	ald Water Cumply: Is	2000				
Household		ater Supply: well ID. ng: how many wells?			e: well ID	ease				
☐ Lawn & Garden		echarge: well ID			☐ Uncased ☐ €					
☐ Livestock	8. 🗌 Monitorir	ng: well ID			nal: how many bores					
2. Irrigation 9. Environmental Remediation: well l										
3. ☐ Feedlot 4. ☐ Industrial	☐ Air Sparg ☐ Recovery	•	or Extraction			scharge				
			Tay Ment.							
Was a chemical/bacter Water well disinfected?		mitted to KDHE? [⊥ Yes ∧ No	ii yes, date sa	mpie was submitte	ed:				
		/C D Other	CASIN	IG IOINTS: 5	₹ Glued □ Clamped	d □ Welded □ Thre	aded			
Casing diameter	in to 350 ft	Diameter	in to	8 TYPE OF CASING USED: Steel PVC Other						
Casing height above land surface										
Casing height above land	surfacei	n. Weight		Wall thicknes	s or gauge No 🏞 .	200				
Casing height above land: TYPE OF SCREEN OF	surface	n.	lbs./ft.	Wall thicknes	s or gauge No Tr	160				
Casing height above land a TYPE OF SCREEN OF Steel ☐ Stair	surface	n. Weight TERIAL: rglass ⊠ PVC	lbs./ft.	Wall thicknes ☐ Other (s or gauge No Tr) <i>0</i> 0				
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv	surface	n. Weight TERIAL: rglass M PVC crete tile □ None	lbs./ft.	Wall thicknes ☐ Other (s or gauge No Tr	160				
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR	surface	n. Weight TERIAL: rglass MEPVC crete tile □ None RE:	lbs./ft.	Wall thicknes	s or gauge No Tr					
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot	surface	n. Weight TERIAL: rglass MAPVC crete tile □ None RE: dauze Wrapped □	lbs./ft. e used (open hole Torch Cut D	Wall thicknes ☐ Other () rilled Holes ☐	ss or gauge No Tr (Specify)					
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot	surface	n. Weight TERIAL: rglass MAPVC crete tile □ None RE: dauze Wrapped □	lbs./ft. e used (open hole Torch Cut D	Wall thicknes ☐ Other () rilled Holes ☐	ss or gauge No Tr (Specify)					
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAGE	surface	n. Weight TERIAL: rglass PVC crete tile None .RE: auze Wrapped vire Wrapped n 220. ft. to 2.50 m. 240. ft. to 3.50	used (open hole Torch Cut Desaw Cut No., ft., From	Wall thicknes Other () rilled Holes one (Open Hole ft. to ft. to	Sor gauge No 7f (Specify) Other (Specify) ft., From	ft. to	ft. ft.			
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAGE GROUT MATERIA	surface	n. Weight TERIAL: rglass PVC crete tile None .RE: auze Wrapped vire Wrapped n. 2.0 ft. to	e used (open hole Torch Cut Desaw Cut Note: Torch ft., From Torch Cut Desaw Cut Note: Torch Cut Desaw	Wall thicknes Other () rilled Holes one (Open Hole ft. to ther	Sor gauge No Tr (Specify) Other (Specify) ft., From ft., From	ft. to	ft. ft.			
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG GROUT MATERIA Grout Intervals: From	surface	n. Weight TERIAL: rglass PVC crete tile None .RE: auze Wrapped vire Wrapped n. 2.0 ft. to	e used (open hole Torch Cut Desaw Cut Note: Torch ft., From Torch Cut Desaw Cut Note: Torch Cut Desaw	Wall thicknes Other () rilled Holes one (Open Hole ft. to ther	Sor gauge No Tr (Specify) Other (Specify) ft., From ft., From	ft. to	ft. ft.			
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possible	surface	n. Weight	Torch Cut Do Saw Cut No ft., From Do Saw Cut No ft. to No ft.	Wall thicknes Other () rilled Holes one (Open Hole ft. to ther	Specify)	ft. to	ft. ft.			
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG GROUT MATERIA Grout Intervals: From	surface	n. Weight	Torch Cut Do Saw Cut No ft., From Do Saw Cut No ft. to No ft.	Wall thicknes Other () rilled Holes one (Open Hole ft. to ther	Other (Specify)	ft. to	ft. ft.			
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Line	surface	n. Weight	Torch Cut Do Saw Cut No ft., From Do Saw Cut No ft. to Do Saw Cut No ft. ft. ft. to Do Saw Cut No ft. ft. ft. ft. ft. ft. ft. ft. ft.	Wall thicknes Other () rilled Holes one (Open Hole	Other (Specify)	ft. to	ft. ft.			
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG 9 GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Lines	surface	n. Weight	Bentonite O ft. to	Wall thicknes Other () rilled Holes one (Open Hole ft. to ther ft., From Livestock Pens Fuel Storage Fertilizer Storage	Sor gauge No	ft. to	ft. ft.			
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG 9 GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well?	surface	n. Weight	Lagoon	Wall thicknes Other () rilled Holes one (Open Hole	Sor gauge No Tr (Specify) Other (Specify) ft., From ft., From Insection Abando a	ft. to	ft. ft.			
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG 9 GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO	surface	n. Weight	Bentonite O ft. to	Wall thicknes Other () rilled Holes one (Open Hole	Sor gauge No Tr (Specify) Other (Specify) ft., From ft., From Insection Abando a	ft. to	ft. ft.			
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG 9 GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO	surface	n. Weight	Bentonite O Lagoon O FROM FROM FROM Lagoon FROM FROM Lagoon FROM FROM FROM Lagoon FROM FROM	Wall thicknes Other () rilled Holes one (Open Hole	Sor gauge No Tr (Specify) Other (Specify) ft., From ft., From Insection Abando a	ft. to	ft. ft.			
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAGE GRAVEL PAGE GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO	surface	n. Weight	Lagoon	Wall thicknes Other () rilled Holes one (Open Hole	Sor gauge No Tr (Specify) Other (Specify) ft., From ft., From Insection Abando a	ft. to	ft. ft.			
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galve SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAGE GRAVEL PAGE GRAVEL PAGE Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? TO FROM TO TO	surface	n. Weight	Bentonite O Lagoon O FROM FROM FROM Lagoon FROM FROM Lagoon FROM FROM FROM Lagoon FROM FROM	Wall thicknes Other () rilled Holes one (Open Hole	Sor gauge No Tr (Specify) Other (Specify) ft., From ft., From Insection Abando a	ft. to	ft. ft.			
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galve SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possible Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 2 60 290 350 350 350	surface	n. Weight	Bentonite O Lagoon O FROM FROM FROM Lagoon FROM FROM Lagoon FROM FROM FROM Lagoon FROM FROM	Wall thicknes Other () rilled Holes one (Open Hole	Sor gauge No Tr (Specify) Other (Specify) ft., From ft., From Insection Abando a	ft. to	ft. ft.			
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galve SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 2 60 60 270 275 350 775 783	surface	n. Weight	e used (open hole Torch Cut Desaw Cut No	Wall thicknes Other () rilled Holes one (Open Hole	Sor gauge No Tr (Specify) Other (Specify) ft., From ft., From Insection Abando a	ft. to	ft. ft.			
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galve SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possible Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 2 60 290 350 350 350	surface	n. Weight	Bentonite O Lagoon O FROM FROM FROM Lagoon FROM FROM Lagoon FROM FROM FROM Lagoon FROM FROM	Wall thicknes Other () rilled Holes one (Open Hole	Sor gauge No Tr (Specify) Other (Specify) ft., From ft., From Insection Abando a	ft. to	ft. ft.			
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galve SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 2 60 60 270 275 350 775 783	surface	n. Weight	e used (open hole Torch Cut Desaw Cut No	Wall thicknes Other () rilled Holes one (Open Hole	Sor gauge No Tr (Specify) Other (Specify) ft., From ft., From Insection Abando a	ft. to	ft. ft.			
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galve SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possible Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 2 60 290 350 350 375 375 375 375 375 375 375 375 375 375	surface	n. Weight	Bentonite One It is swater Notes: Distribution of the benefit of	Wall thicknes Other () rilled Holes one (Open Hole one (Open Hole one (T. to one of the to one of the to one of the other one of the othe	Sor gauge No	ft. to	ft. ft.			
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galve SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 2 60 60 270 275 775 783 787 787	surface	n. Weight	Bentonite O Lagoon O FROM Notes: Notes:	Wall thicknes Other () rilled Holes one (Open Hole fit to fit. to fit. to fit. to fit. The	Sor gauge No	ft. to	ft. ft.			
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galve SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 2 60 60 270 275 775 783 787 787	surface	n. Weight	Bentonite O Lagoon O FROM Notes: Notes:	Wall thicknes Other () rilled Holes one (Open Hole one (Open Hole one ft. to one ft. T	Sor gauge No	ft. to	ft. ft.			
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG GRAVEL PAG	surface	n. Weight	Bentonite O Lagoon O FROM Notes: Notes:	Wall thicknes Other () rilled Holes one (Open Hole one (Open Hole one ft. to one ft. T	Sor gauge No	ft. to	ft. ft.			

KSA 82a-1212

Visit us at http://www.kdheks.gov/waterwell/index.html

Revised 9/10/2012