


1 LOCATION OF WATER WELL: Fraction NW 1/4 NW 1/4 SW 1/4 Section Number 35 Township Number T 31 S Range Number R 34 EW

Distance and direction from nearest town or city street address of well if located within city?
 Approximately 9 1/2 miles South & 1/2 mile West of Satanta.

2 WATER WELL OWNER: Sweetman Drilling
 RR#, St. Address, Box #: 110 S. Main, Suite 500 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Wichita, Ks. 67202 Application Number: T88-525

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 190 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield 100 gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter 10 5/8 in. to 190 ft., and in. to ft.
 WELL WATER TO BE USED AS:
 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes.....No...X.....; If yes, mo/day/yr sample was sub-
 mitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 6 in. to 190 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface 12 in., weight 4.129 lbs./ft. Wall thickness or gauge No. 316
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 130' ft. to 190' ft., From ft. to ft.
 From ft. to ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 20' ft. to 190' ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 20' ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? Southeast How many feet? 175'

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
		See log attached			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/21/88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 145 This Water Well Record was completed on (mo/day/yr) 10/28/88 under the business name of Henkle Drilling & Supply Company, Inc. by (signature) *Bruce Richmitt*

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

DRILLERS TEST LOG

CUSTOMER'S NAME: Sweetman Drilling DATE: 10/21/88
 STREET ADDRESS: 110 South Main, Suite 500 TEST # 1 E. LOG Yes
 CITY & STATE: Wichita, Ks. 67202 DRILLER Shelden
 COUNTY Seward QUARTER SW SECTION 35 TOWNSHIP 31 RANGE 34

LOCATION _____

Z	FOOTAGE			DESCRIPTION OF STRATA	STATIC WATER LEVEL:	
	From	Pay	TO		Proposed Well Depth:	
	0		2	Top Sand.		
	2		6	Fine sand & cobblestones.		
	6		95	Brown sandy clay & few sand streaks.		
70	95	17	112	Sand fine to medium coarse. Small to large gravel.		
	112		122	Brown sandy clay.		
70	122	68	190	Sand fine to medium coarse. Small to medium gravel with few small clay streaks.		
	190		260	Brown sandy clay & fine sand streaks with Limerock streaks		
				6" PVC		
				PLAIN	PERF	
				190' - 130'	60'	
				130' - 0	130'	
				Total	130'	60'
				3 - 50# Bags of Hi-Tek		
				6 - 50# Bags Hole Plug		
				2 - 6" Caps		
				9 - Centralizers		

21
24
27
04
05
04

RECEIVED
 JAN 27 1989
 DIVISION OF ENVIRONMENT