WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

1. Location of well:	County Fraction Stevens SW 1/4 SW 1/4 SW			Section	number	Township number Range number					
1. Location of well:				1	7	т 31	5	S R	35	<u>₹</u> /W	
					Owner of well: Omar Norton						
10. 11. 12. 12. 12. 14. 14. 14. 14. 14. 14. 14. 14. 14. 14					Moscow, Kansas 67952						
Mouture City, state, 21p code							- 1				
4. Locate with "X" in section below: Sketch map:						6. Bore hole dia. 22 in. Completion date Well depth 524 ft. 7–19–76					
·						X Cable tool X Rotary _ Driven _ Dug					
						Hollow rod Jetted Bored Reverse rotary					
'						8. Use: X Domestic Public supply Industry					
₩						Irrigation Air conditioning Stock Lawn Oil field water Other					
						9. Casing: Material PUC Height: Above or					
						Threaded Welded Surface in.					
s						RMPPVCWeightIbs./ft. Dia. 3 in. to 324 ft. depth Wall Thickness: inches or					
1				T	+	Diain. to _	≥7 ft. de	epth Wal	I Thickness: e No	265	
5. Type and color of	f material			From	То	10. Screen: Man	ufacturer's	name _	,		
					_	Jes	<u>s & L</u>	owel	1	- /-	
Top soil				0	6		1/8	Dia.	th	20	
Tan clay				7	110	1				ft.	
				111	116	Gravel pack?	go - ft.	and		ft.	
Fine san	<u>.u</u>			TIL	110	11. Static water I		ange of		mo./day/yr.	
Tan clay				117	125	305_ft. be		urface [
Med. to very fine soft streaks				126	270	12. Pumping leve	l below la	nd surfac	es:		
med. to very line soft streaks				120	210	ft. after		hrs. pur	mping	g.p.m.	
Clay				271	281	Estimated maximu				g.p.m.	
Sandy clay				282	298					mo./day/yr.	
Sundy Or	Ct. /					Yes XX		Date			
Limestone				299	300		npletion:		Inches abo	ve grade	
Sandy clay				301	320	Y Pitless sales			menes and	,,, a,	
				201	222	With: Neat	cement	Ben		Concrete	
Limestone				321	322	Depth: From4	ft. t	<u>-14</u>	ft.		
Med. to very fine sand				323	340	16. Nearest source fr. <u>70</u> Di	e of possil	ble conto	mination:	old wel	
_				341	347	Well disinfected	upon comp	letion?	XX Yes	No	
Limeston	Limestone				J4/	17. Pump:		_	Not install		
Sandy cl	Sandy clay			348	410	Manufacturer's no Model number	splo		otor_	Volts 220	
Tight wi	th mad, to very fi	ne soft streeks		411	490	Length of drop pi	,		capacity _		
Tight with med. to very fine soft streaks						Type:					
Clay, yellow				491	496	4	e			bine iprocating	
Fine san	1d (Use a second	sheet if needed)		497	543	Jet Centrifug	ai i		O+	, -	
18. Elevation: 19. Remarks:						20. Water well a	ontractor'	s certific	ation:		
						This well was dri		, ,			
Topography:						is true to the best	,	•	and belief.		
Hill						Eriesen Business name	Winds	01 I I		252 License No.	
Slope						Address —	adger	Kans	as (67864	
X Upland Valley						Signed Ay	forized r	epresento	ntive D	ate 8 6 7	