

1 LOCATION OF WATER WELL: County: Stevens		Fraction 1/4 C/SE 1/4 SE 1/4		Section Number 11	Township Number T 31 S	Range Number R 35 EW
Distance and direction from nearest town or city street address of well if located within city? 6 3/4NE of Moscow, KS						
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		Sweetman Drilling 110 S. Main, Suite 500 Wichita, KS 67202			#2-11 Dunlap A Board of Agriculture, Division of Water Resources Application Number: 930028	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: <div style="text-align: center;"> </div>		4 DEPTH OF COMPLETED WELL 340 ft. ELEVATION: Depth(s) Groundwater Encountered 1 160 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 160 ft. below land surface measured on mo/day/yr 1/01/93 Pump test data: Well water was 260 ft. after 1 hours pumping 90 gpm Est. Yield 90 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 11 in. to 340 ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes YES No				
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS		5 Wrought iron 8 Concrete tile 6 Asbestos-Cement 9 Other (specify below) 7 Fiberglass		CASING JOINTS: Glued X Clamped Welded Threaded		
Blank casing diameter 6 in. to 340 ft. Dia in. to ft. Dia in. to ft.		Casing height above land surface 24 in. weight 2.902 lbs./ft. Wall thickness or gauge No. 280 SDR21				
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		10 Asbestos-cement 11 Other (specify) 12 None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 2 Louvered shutter 4 Key punched		5 Gauzed wrapped 8 Saw cut 11 None (open hole) 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)				
SCREEN-PERFORATED INTERVALS: From 260 ft. to 340 ft. From ft. to ft. From ft. to ft. From ft. to ft.						
GRAVEL PACK INTERVALS: From 140 ft. to 340 ft. From ft. to ft. From ft. to ft. From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Hole Plug		Grout Intervals: From 1 ft. to 20 ft. From ft. to ft. From ft. to ft.				
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage		Direction from well? East How many feet? 200				
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS
0	2	Surface Soil				
2	54	Sandy Clay				
54	59	Clay				
59	88	Sandy Clay				
88	227	Sand & Gravel				
227	231	Clay				
231	259	Sand				
259	271	Clay				
271	340	Sand				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1/01/93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. KWWCL-430 This Water Well Record was completed on (mo/day/yr) 1/01/93 under the business name of Howard Drlg. Co. Box 806 Beaver, OK 73932 by (signature)						

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.