


1 LOCATION OF WATER WELL: Fraction NW 1/4 SE 1/4 SW 1/4 Section Number 27 Township Number T 31 S Range Number R 35 EW
 County: Stevens Distance and direction from nearest town or city street address of well if located within city? From Woods go 10 mi North 1/2 mi West and North into location.

2 WATER WELL OWNER: Clay Kauffman Mobil Oil Corp.
 RR#, St. Address, Box #: 1238 South Parton Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Santa Ana, Calif. 92707 Application Number: T 87-52

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 460 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 202 ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL: 258 ft. below land surface measured on mo/day/yr 2/16/87
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield: 100 gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter: 11 in. to 460 ft. and in. to ft.
 WELL WATER TO BE USED AS:
 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 6 5/8 in. to 280 ft., Dia. in. to ft., Dia. in. to ft.
 Casing height above land surface: 28 in., weight 2.85 lbs./ft. Wall thickness or gauge No. 265
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 280 ft. to 460 ft. From ft. to ft.
 GRAVEL PACK INTERVALS: From 240 ft. to 460 ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? Southeast of water well How many feet? 200'

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	surface	423	438	60% clay, 20% gravel & 20% sandstone
2	43	clay & caliche	438	460	white gipp rock & sandstone
43	48	fine sand			
48	83	clay			
83	131	sandy clay			
131	206	med. to large sand			
206	213	clay			
213	230	gravel			
230	246	med. to large sand			
246	253	50% clay & 50% med. to large sand			
253	321	10% med. to lg. sand & 90% sandy clay			
321	348	clay & fine sand			
348	423	med. to large sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) February 16, 1987 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 118 This Water Well Record was completed on (mo/day/yr) February 25, 1987 under the business name of Carlile Water Well Service, Inc. by (signature)