


1 LOCATION OF WATER WELL: Fraction ~~NW~~ ^{NW} $\frac{1}{4}$ NW $\frac{1}{4}$ ~~NE~~ ^{NE} $\frac{1}{4}$ Section Number 36 Township Number T 31 S Range Number R 35 EW

Distance and direction from nearest town or city street address of well if located within city? from Woods, KS, 10 Miles North, 1 1/2 Miles East, South into location.

2 WATER WELL OWNER: Jim & Kay Wilder MCCOY PETRO.
 RR#, St. Address, Box #: 8347 Mitzie Drive Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Denver, Colorado 80221 Application Number: T89-349

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL 480 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 230 ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr 7-31-89
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter 11 in. to 480 ft., and in. to ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well
 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 6 5/8" in. to 320 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface -60 in., weight lbs./ft. Wall thickness or gauge No.
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 320 ft. to 480 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 27 ft. to 300 ft., From 310 ft. to 420 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 5 ft. to 7 ft., From 7 ft. to 27 ft., From 300 ft. to 310 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? Northwest How many feet? 270

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
			0	5	Backfill
			5	7	Neat Cement
			7	27	Bentonite Grout
			27	300	Chlorinated Gravel
			300	310	Bentonite Grout
			310	480	Chlorinated Gravel
					PVC Cap glued on top of casing @ 5' below ground level, cemented over, then backfilled.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-29-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 118 This Water Well Record was completed on (mo/day/yr) 10-02-89 under the business name of Carlile Water Well Service, Inc. by (signature)

OFFICE USE ONLY
T
R
EW
SEC.