


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: STEVENS	C 1/4 SE 1/4 SE 1/4	10	T 31 S	R 36W EW

Distance and direction from nearest town or city street address of well if located within city?

2 1/2 MILES NORTH MOSCOW, KS

2 WATER WELL OWNER: ANADARKO PET.	#1 LAHEY "B" Board of Agriculture, Division of Water Resources Application Number: 960049
RR#, St. Address, Box #: BOX 351	
City, State, ZIP Code: LIBERAL, KS 67905-0351	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 420 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 160 ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 160 ft. below land surface measured on mo/day/yr 02-08-96
	Pump test data: Well water was 180 ft. after 1 hours pumping 90 gpm
	Est. Yield 90 gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 11 in. to 420 ft., and in. to ft.
	WELL WATER TO BE USED AS:
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below)
	Was a chemical/bacteriological sample submitted to Department? Yes.....No... X; If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded	
2 PVC 4 ABS 7 Fiberglass Threaded	
Blank casing diameter 6 in. to 420 ft., Dia in. to ft., Dia in. to ft.	
Casing height above land surface 24 in., weight 2.902 lbs./ft. Wall thickness or gauge No. 280 SDR 21	
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:	8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 320 ft. to 420 ft., From ft. to ft., From ft. to ft.	
GRAVEL PACK INTERVALS: From 220 ft. to 420 ft., From ft. to ft., From ft. to ft.	

6 GROUT MATERIAL:	1 Neat cement 2 Cement grout 3 Bentonite 4 Other HOLE PLUG
Grout Intervals: From 0 ft. to 16 ft., From ft. to ft., From ft. to ft.	
What is the nearest source of possible contamination:	10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage	
Direction from well? Northeast	How many feet? 2000

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	36	SANDY CLAY	377	420	SAND & SAND STONE & CLAY STREAKS
36	41	CLAY			
41	97	CLAY & SANDY CLAY			
97	122	SANDY CLAY & CALICHE STREAKS			
122	156	SANDY CLAY & SAND STREAKS			
156	184	SAND			
184	192	CLAY & SAND STREAKS			
192	262	SAND			
262	275	SAND & SANDY CLAY STREAKS			
275	287	SANDY CLAY			
287	313	BLUE CLAY			
313	324	FINE SAND			
324	366	CLAY & SANDY CLAY			
366	374	FINE SAND			
374	377	SANDY CLAY			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 02-08-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. KWWCL-430 This Water Well Record was completed on (mo/day/yr) 02-08-96 under the business name of HOWARD DRILG.CO.BOX 806 BEAVER, OK 73932 by (signature) <i>Howard Drilg</i>
