


1 LOCATION OF WATER WELL: Fraction NW 1/4 SE 1/4 SE 1/4 Section Number 23 Township Number T 31 S Range Number R 36 E/W  
 County: Stevens

Distance and direction from nearest town or city street address of well if located within city?  
 1 East .8 South of Moscow

2 WATER WELL OWNER: Grandstaff 1-23 Ensign Operating CO  
 RR#, St. Address, Box #: 621 17th Street Ste 1800 Board of Agriculture, Division of Water Resources  
 City, State, ZIP Code: Denver, CO 80293 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
  
 4 DEPTH OF COMPLETED WELL: 390 ft. ELEVATION:  
 Depth(s) Groundwater Encountered 1. 125 ft. 2. ft. 3. ft.  
 WELL'S STATIC WATER LEVEL: 265 ft. below land surface measured on mo/day/yr 7-31-91  
 Pump test data: Well water was 280 ft. after 2 hours pumping 60 gpm  
 Est. Yield 65 gpm: Well water was ft. after hours pumping gpm  
 Bore Hole Diameter: 9 in. to 390 ft., and in. to ft.  
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well  
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped  
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded  
 7 Fiberglass Threaded  
 Blank casing diameter 5 in. to 290 ft., Dia in. to ft., Dia in. to ft.  
 Casing height above land surface 14 in., weight 200 lbs./ft. Wall thickness or gauge No. 0.265  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)  
 9 ABS 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify)  
 SCREEN-PERFORATED INTERVALS: From 290 ft. to 390 ft., From ft. to ft.  
 GRAVEL PACK INTERVALS: From 250 ft. to 390 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grout Intervals: From 20 ft. to 0 ft., From ft. to ft., From ft. to ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage  
 Direction from well? Southwest How many feet? 250

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	265	Overburden			
265	300	Clay			
300	320	Fine sand and clay			
320	340	Clay			
340	360	Fine sand and clay			
360	380	Clay and streaks of medium sand			
380	390	Fine sand and claystreaks			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-31-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 142 This Water Well Record was completed on (mo/day/yr) 8-12-91 under the business name of T & W Water Well Service, Inc. by (signature) *C. W. Wagoner*

OFFICE USE ONLY T R E/W SEC 1/4 1/4 1/4