


1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number			
County: Morton		NW ¼ SW ¼ SE ¼		31		T 31 S		R 39 E/W			
Distance and direction from nearest town or city street address of well if located within city? West of Moscow to Dermont School 2 South ½ West ¼ North 1/8 West South into											
2 WATER WELL OWNER: Milburn A-2 OXY USA INC RR#, St. Address, Box #: Box 26100 City, State, ZIP Code: Oklahoma City, OK Board of Agriculture, Division of Water Resources Application Number:											
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:				4 DEPTH OF COMPLETED WELL: 300 ft. ELEVATION:							
<div style="text-align: center;"></div>				Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.							
				WELL'S STATIC WATER LEVEL 192 ft. below land surface measured on mo/day/yr 5-5-91							
				Pump test data: Well water was ft. after hours pumping gpm							
				Est. Yield gpm: Well water was ft. after hours pumping gpm							
Bore Hole Diameter: in. to ft., and in. to ft.				WELL WATER TO BE USED AS:							
				5 Public water supply 8 Air conditioning 11 Injection well							
				1 Domestic 3 Feedlot <u>6 Oil field water supply</u> 9 Dewatering 12 Other (Specify below)							
				2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well							
Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> If yes, mo/day/yr sample was submitted											
Water Well Disinfected? Yes No <input checked="" type="checkbox"/>											
5 TYPE OF BLANK CASING USED:											
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped											
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded											
7 Fiberglass Threaded											
Blank casing diameter 5 in. to 200 ft., Dia in. to ft., Dia in. to ft.											
Casing height above land surface in., weight lbs./ft. Wall thickness or gauge No.											
TYPE OF SCREEN OR PERFORATION MATERIAL:											
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement											
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)											
12 None used (open hole)											
SCREEN OR PERFORATION OPENINGS ARE:											
1 Continuous slot 3 Mill slot 5 Gauzed wrapped <u>8 Saw cut</u> 11 None (open hole)											
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes											
7 Torch cut 10 Other (specify)											
SCREEN-PERFORATED INTERVALS: From 200 ft. to 300 ft., From ft. to ft.											
GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft.											
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout <u>3 Bentonite</u> 4 Other											
Grout Intervals: From 182 ft. to 205 ft., From 23 ft. to 3 ft., From ft. to ft.											
What is the nearest source of possible contamination:											
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well											
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well											
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)											
13 Insecticide storage											
Direction from well? South How many feet? 300											
FROM		TO		LITHOLOGIC LOG		FROM		TO		PLUGGING INTERVALS	
						0		3		Topsoil	
						3		23		Bentonite	
						23		182		Sand	
						182		205		Bentonite	
						205		300		Sand	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-30-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 142 This Water Well Record was completed on (mo/day/yr) 5-31-91 under the business name of T & W Water Well Service, Inc. by (signature) <i>C. W. Wagoner</i>											