


1 LOCATION OF WATER WELL: Fraction Section Number Township Number Range Number  
 County: Morton SW ¼ SW ¼ SW ¼ 21 T 31 S R 40 EW

Distance and direction from nearest town or city street address of well if located within city?  
 4 miles north, 5 miles east of Richfield, Kansas

2 WATER WELL OWNER: Seaboard Farms, Inc. S-3, Breeding #1, well #2  
 RR#, St. Address, Box #: P. O. Box 1029 Board of Agriculture, Division of Water Resources  
 City, State, ZIP Code: Hugoton, Kansas 67951 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
  
 4 DEPTH OF COMPLETED WELL: 398 ft. ELEVATION: slope  
 Depth(s) Groundwater Encountered 1. 187 ft. 2. ft. 3. ft.  
 WELL'S STATIC WATER LEVEL 187 ft. below land surface measured on mo/day/yr 12/11/95  
 Pump test data: Well water was ft. after hours pumping gpm  
 Est. Yield gpm: Well water was ft. after hours pumping gpm  
 Bore Hole Diameter 26 in. to 398 ft. and in. to ft.  
 WELL WATER TO BE USED AS:  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well  
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped  
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X  
 7 Fiberglass Threaded  
 Blank casing diameter 12 in. to 194.4 ft., Dia. in. to ft., Dia. in. to ft.  
 Casing height above land surface 17 in., weight 25.22 lbs./ft. Wall thickness or gauge No. 188  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify)  
 SCREEN-PERFORATED INTERVALS: From 194.4 ft. to 398 ft. From ft. to ft.  
 From ft. to ft. From ft. to ft.  
 GRAVEL PACK INTERVALS: From 24 ft. to 398 ft. From ft. to ft.  
 From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From ft. to ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage  
 Direction from well? north How many feet? 200

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Surface			
2	40	Clay			
40	70	Sandy clay			
70	120	Medium sand w/clay breakers			
120	190	Coarse sand			
190	210	Yellow chalkw/sandrock			
210	230	Yellow chalk w/fine sandstone			
230	261	Fair sandstone			
261	293	XXXXXX			
261	320	Yellow chalk w/tight sandstone			
320	358	Brown and red shale w/red sandrock			
358	361	Good sandstone			
361	393	Brown and red shale w/tight sandstone strips			
393	410	Brown and red shale w/hard sandstone			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/8/95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 164 This Water Well Record was completed on (mo/day/yr) 11/12/95 under the business name of Houck Bros. Drilling Co. by (signature) M. Beard