

1 LOCATION OF WATER WELL: County: <u>Morton</u>	Fraction <u>NW 1/4 NW 1/4 NW 1/4</u>	Section Number <u>28</u>	Township Number T <u>31</u> S	Range Number R <u>40</u> EW
--	---	-----------------------------	----------------------------------	--------------------------------

Distance and direction from nearest town or city street address of well if located within city?

20 Miles NW Rolla Mo.

2 WATER WELL OWNER: <u>Saaboard Corp.</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: <u>US 54</u>	Application Number:
City, State, ZIP Code: <u>Guyman, Oklahoma</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>193.0</u> ft. ELEVATION:
--	--

Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 182.6 ft. below land surface measured on mo/day/yr 7-22-96

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield 100 gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 16 in. to 193.0 ft. and in. to ft.

WELL WATER TO BE USED AS:

1 Domestic	3 Feedlot	5 Public water supply	8 Air conditioning	11 Injection well
2 Irrigation	4 Industrial	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
7 Lawn and garden only 10 Monitoring well				

Was a chemical/bacteriological sample submitted to Department? Yes No ☒; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No ☒

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped
------------------------------	----------------	-----------------	--

1 Steel 3 RMP (SR)

☒ PVC 4 ABS

7 Fiberglass

6 Asbestos-Cement 9 Other (specify below)

Welded

Threaded

Blank casing diameter 10 in. to 133.5 ft., Dia. in. to ft., Dia. in. to ft.

Casing height above land surface 24 in., weight lbs./ft. Wall thickness or gauge No. Sch 40, BE

TYPE OF SCREEN OR PERFORATION MATERIAL:	10 Asbestos-cement
---	--------------------

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS

11 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot ☒ Mill slot

2 Louvered shutter 4 Key punched

5 Gauzed wrapped 8 Saw cut 11 None (open hole)

6 Wire wrapped 9 Drilled holes

7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 133.5 ft. to 187.5 ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 193.0 ft. to 110.0 ft., From ft. to ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	<input checked="" type="radio"/> Other <u>Enviro Plug</u>
-------------------	---------------	----------------	-------------	---

Grout Intervals: From 110.0 ft. to 0.0 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines 7 Pit privy

2 Sewer lines 5 Cess pool 8 Sewage lagoon

3 Watertight sewer lines 6 Seepage pit 9 Feedyard

10 Livestock pens 14 Abandoned water well

11 Fuel storage 15 Oil well/Gas well

12 Fertilizer storage 16 Other (specify below)

13 Insecticide storage

Direction from well? Unknown How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	25	Silty Sandy Clay Brown-Red & Yellow			
25	40	Red Sandy Clay			
40	59	Lt. Gray Red Silty Clay w/caliche			
59	65	Fine to Med. Sand & Med. Gravel			
65	74	Red & Brown Clay Sand & Gravel layers			
74	103	Yellow Sandy Clay			
103	137	Lt. Brown Sandy Clay w/caliche			
137	140	Fine to Med. Sand			
140	155	Fine to Coarse Sand w/small Gravel			
155	182	Fine to Med. Sand			
182	191	Lt. Brown Sandy Clay			
191	193	Red Brown Sandy Clay			
	7.0.				

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <input checked="" type="checkbox"/> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>7-21-96</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>501</u> This Water Well Record was completed on (mo/day/yr) <u>8-16-96</u> under the business name of <u>Layne Western Co</u> by (signature) <u>Steve Mitchell</u>
--