


USE TYPEWRITER OR BALL  
POINT PEN-PRESS FIRMLY,  
PRINT CLEARLY.

WATER WELL RECORD  
KSA 82a-1201-1215

3143W117 NENW  
T R EW sec 1/4 1/4 1/4 No.

Kansas State Dept. Of Health  
(Water Well Contractors)  
Forbes-Bldg. 740  
Topeka, Kansas 66620

1 Location of well:		County	Township name	Fraction	Section number	Town number	Range number
		Morton	Westola	<del>S. 1/4</del>	17	31	43
Distance and direction from nearest town or city:				3 Owner of well: Abner Delay			
Street address of well location if in city:				Address: Mantor, KS 67862			
Locate with "X" in section below: N  W E S 1 Mile				Sketch map:			
				4 Well depth: 130 ft. Date of completion 12-31-74 Well diameter 13 in.			
				5 <input type="checkbox"/> Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary			
				6 Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Commercial <input type="checkbox"/> Test well <input type="checkbox"/>			
				7 Casing: Material PVC Height: above/below Threaded <input type="checkbox"/> Welded <input type="checkbox"/> Surface 12 in. Diam. 10 in. to 130 ft. depth Drive shoe? <input type="checkbox"/> Yes <input type="checkbox"/> No in. to ft. depth			
2 Type and color of material				From	To	8 Screen: Alyssa Irrigation Pipe Co. Manufacturer Perforated by drill Type PVC Dia. 10 1/4 Slot/gauze 4 x 3 Length 20 Set between 50 ft. and 130 ft. Fittings: Gravel pack <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Size range of material 4"	
Surface Soil + Subsoil				0	20	9 Static water level: 45 ft. below land surface Date 12-31-74	
Sandy clay				20	22	10 Pumping level below land surfaces: ft. after hrs. pumping g.p.m. ft. after hrs. pumping g.p.m. Estimated maximum yield 200 g.p.m.	
Sand				22	38	11 Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date	
Sand & Gravel				38	60	12 Well head completion: <input type="checkbox"/> Pitless adapter 12 inches above grade	
Yellow Sandy clay				60	72	13 Well grouted? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> Mortar cement <input type="checkbox"/> Bentonite Depth: From 0 ft. to 22 ft.	
Gravel				72	80	14 Nearest source of possible contamination: ft. Direction N 80° E Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
Sand Stone & Brown - Soft-in-stre				80	120	15 Pump: <input type="checkbox"/> Not installed Manufacturer's name Fairbanks Morse's Model number 75663 HP 7.5 Volts 224 Length of drop pipe ft. capacity 200 g.m.p. Type: <input checked="" type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other	
Blue Shale				120	130		
(use a second sheet if needed)							
16 Remarks: elevation				17 Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Delay Drilling 231 Business name License No. Address Mantor, Kansas Signed Abner Delay Date 1-80-75 Authorized representative			