	WATED	WELL RECORD	Form WWC-5	KSA 82a	1212 Well #	2-34	
LOCATION OF WATER WELL:	Fraction		Section	n Number	Township Nur	nber	Range Number
ounty: HAYDEN	1.5E 1/4	SE 14 NE		3	T 3/	S	R 6 EM
istance and direction from nearest town		ress of well if located	within city?	~ · ·	11	1. /	a
2 MI NE OF HAMPEN K	15 then	5HL NON	Murdock	Rd to	SE 180 ST	then (for Mile.
WATER WELL OWNER: 11 ASTE	CONNECT	TONS. INC.					
	50419 R				Board of Ag	riculture, Di	vision of Water Resource
ity, State, ZIP Code : EKIAI	horst City	OK 73179			Application 1	Number:	
LOCATE WELL'S LOCATION WITH 4			24	ft. ELEVA	TION:		
AN "X" IN SECTION BOX:	epth(s) Groundwa	ater Encountered 1.					
[] [v	VELL'S STATIC V	NATER LEVELん	55 ft. bel	ow land sur	face measured on r	no/day/yr	4-23-02
	Pump	test data: Well water	rwas	ft. a	fter	hours pum	nping gpm
NW NE	st Yield	gpm: Well wate	r was	ft. a	fter	hours pum	nping gpm
	Rore Hole Diamete	er 6.5 in to.	24	. ,	and	in.	to
· \	VELL WATER TO		5 Public water		8 Air conditioning		njection well
	1 Domestic	3 Feedlot	6 Oil field wate	r supply	9 Dewatering	2.620	Other (Specify below)
SW SE	2 Irrigation	4 Industrial	7 Lawn and ga	rden only	10 Monitoring well	FIE 20	MELER
	Mae a chemical/ha	acteriological sample s	submitted to Der	artment? Y	esNo.	; If yes, r	mo/day/yr sample was sub
	•	acteriological sample s	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Wa	ter Well Disinfected	? Yes	No 🗾
	nitted	5 Wrought iron	8 Concret				Clamped
TYPE OF BLANK CASING USED:		6 Asbestos-Cement	-	pecify below		Welde	
1 Steel 3 RMP (SR)	•		•		· · · · · · · · · · · ·		ded
2 PVC 4 ABS	24	7 Fiberglass					n. to ft.
Slank casing diameter	n. to ~ ろカ	n., weight		lhe	ft Wall thickness o	r gauge No	Sch 40
asing height above land surface		n., weight	/DPVC			stos-cemer	
YPE OF SCREEN OR PERFORATION						r (specify) .	
1 Steel 3 Stainless		5 Fiberglass	8 RMF 9 ABS	` '		used (ope	
2 Brass 4 Galvanize		6 Concrete tile			8 Saw cut		11 None (open hole)
SCREEN OR PERFORATION OPENING			ed wrapped		9 Drilled holes		(1) (tollo (opoli lioto)
1 Continuous slot			wrapped				
	y punched	7 Torch		4 F			»
SCREEN-PERFORATED INTERVALS:		/. 4/. ft. to	4. 7	π., Fro	m)
	From	. 🛥),
GRAVEL PACK INTERVALS:		.2 ft. to	· · · * * * * * · · · · · ·			ft. to	
	From	ft. to		ft., Fro			
GROUT MATERIAL 1 Neat co	ement 2	Cement group	3 Bentor		_		. ft. to
	t. to 	, π., From	1 ~				pandoned water well
What is the nearest source of possible of	contamination:	JONE UPSETVE	<i>a</i>)		stock pens		i well/Gas well
1 Septic tank 4 Latera		7 Pit privy		11 Fuel			
2 Sewer lines 5 Cess		8 Sewage lage	oon		lizer storage	16 01	ther (specify below)
3 Watertight sewer lines 6 Seepa	ige pit	9 Feedyard			cticide storage		
Direction from well?					iny feet?	UGGING IN	JTERVALS
FROM TO	LITHOLOGIC L	.OG	FROM	то		oddiita ii	TEHVICO
D 1.5 Silt		D (11)					
1.5 4.5 Complet	y weather	ed Siltstone					
4.5 24 SI/ESTONE	<u> </u>						•
			_				
	·						
7 CONTRACTOR'S OR LANDOWNER	'S CERTIFICATIO	DN: This water well w	vas (1) construc	ted, (2) rec	onstructed, or (3) p	lugged und	er my jurisdiction and wa
completed on (mo/day/year)	5/10/07			and this rec	ord is true to the be	st of my kry	wedge and belief. Kansa
	355	This Water V				6-3	-DD()
Water Well Contractor's License No	1000				K	<i>t L 4</i>	Total V