


LOCATION OF WATER WELL: Fraction SW 1/4 SW 1/4 NW 1/4 Section Number 3 Township Number T 31 S Range Number R 6 E (NW)

Distance and direction from nearest town or city street address of well if located within city? 2 mi. NE of Harper KS, then 5 mi. N on Muddack Rd. to SE 180<sup>th</sup> turn R for 1 mi.

WATER WELL OWNER: Waste Connections, Inc.  
 RR#, St. Address, Box #: 4625 South Rockwell  
 City, State, ZIP Code: OKLAHOMA CITY, OK 73179  
 Board of Agriculture, Division of Water Resources  
 Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



DEPTH OF COMPLETED WELL: 51 ft. ELEVATION:  
 Depth(s) Groundwater Encountered 1. 9.1 ft. 2. ft. 3. ft.  
 WELL'S STATIC WATER LEVEL 41.97 ft. below land surface measured on mo/day/yr 4-23-02  
 Pump test data: Well water was ft. after hours pumping gpm  
 Est. Yield < 1 gpm: Well water was ft. after hours pumping gpm  
 Bore Hole Diameter 10 in. to 20 ft., and 6 1/2 in. to 6.0 ft.  
 WELL WATER TO BE USED AS:  
 5 Public water supply 8 Air conditioning 11 Injection well  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well PIEZOMETER  
 Was a chemical/bacteriological sample submitted to Department? Yes.....No.....; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes No

TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped  
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded  
 7 Fiberglass Threaded X

Blank casing diameter 2 in. to 4 1/2 ft., Dia. in. to ft., Dia. in. to in. to ft.  
 Casing height above land surface 30 in., weight lbs./ft. Wall thickness or gauge No. Sch 40

TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)  
 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 41 ft. to 51 ft., From ft. to ft.  
 From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 38 ft. to 53 ft., From ft. to ft.  
 From ft. to ft., From ft. to ft.

GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grout intervals: From 35 ft. to 38 ft., From Point Above ft. to 35 ft., From 0 ft. to 10 ft.

What is the nearest source of possible contamination: (None observed)  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Silty clay, low plasticity	51	60	Back filled w/ granular bentonite
2	6	Completely weathered siltstone			
6	60	Siltstone, firm			

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/10/02 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 555 This Water Well Record was completed on (mo/day/yr) 4-23-02 under the business name of A.W. Pool, Inc. by (signature) [Signature]