


Well # P2-21

LOCATION OF WATER WELL: Fraction NW 1/4 SE 1/4 NE 1/4 Section Number 3 Township Number T 31 S Range Number R 6 E
 County: HARPER
 Distance and direction from nearest town or city street address, of well if located within city?
2 MI NE OF HARPER, KS, then 5 mi N ON MURDOCK RD. to SE 180th St, then R for 1 mi
 WATER WELL OWNER: WASTE CONNECTIONS, INC.
 RR#, St. Address, Box #: 4625 South Rockwell
 City, State, ZIP Code: OKLAHOMA CITY, OK 73179
 Board of Agriculture, Division of Water Resources
 Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



DEPTH OF COMPLETED WELL: 20 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 10.6 ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL 11.87 ft. below land surface measured on 4/23/02
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield 4 gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter 8 in. to 22 in. to in. to ft.
 WELL WATER TO BE USED AS:
 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 Blank casing diameter 2 in. to 10 ft., Dia. in. to ft., Dia. in. to ft.
 Casing height above land surface 30 in., weight lbs./ft. Wall thickness or gauge No. Sch 40

TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 10 ft. to 20 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 8 ft. to 22 ft., From ft. to ft.

3) GROUT MATERIAL 3 1 Neat cement 2 Cement grout 2 3 Bentonite 4 Other
 Grout Intervals: From 6 ft. to 8 ft., From 0 ft. to 6 ft., From ft. to ft.
 What is the nearest source of possible contamination: (NONE.)
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>1</u>	<u>SITE</u>			
<u>1</u>	<u>11</u>	<u>Completely weathered siltstone</u>			
<u>11</u>	<u>22</u>	<u>SILTSTONE BIRM</u>			

7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/10/02 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 535 This Water Well Record was completed on (mo/day/yr) 6-3-02 under the business name of AW POOL, INC by (signature) Keith Pool