


Well # PZ-25

LOCATION OF WATER WELL: Fraction SW 1/4 SE 1/4 NW 1/4 Section Number 3 Township Number T 31 S Range Number R 6 E (N)

Distance and direction from nearest town or city street address of well if located within city?
 2 mi. NE of Harper, KS then 5 mi N on Murdock Rd. to SE 180th St then (R) for 1 mi.

WATER WELL OWNER: Waste Conversions, Inc
 R#, St. Address, Box #: 4605 So. Rockwell
 City, State, ZIP Code: Oklahoma City, OK 73179
 Board of Agriculture, Division of Water Resources
 Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



DEPTH OF COMPLETED WELL: 80 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 70.9 ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL: 78.9 ft. below land surface measured on mo/day/yr 4/23/02
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield 41 gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter: 10 in. to 22 ft., and 6 1/2 in. to 80 ft.
 WELL WATER TO BE USED AS:
 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No (checked); If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No (checked)

TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC (checked) 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded (checked X)

Blank casing diameter: 2 in. to 70 ft., Dia. in. to ft., Dia. in. to ft.
 Casing height above land surface: 30 in., weight lbs./ft. Wall thickness or gauge No. Sch 40

TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 2 Mill slot 3 Mill slot 4 Key punched 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 6 Wire wrapped 9 Drilled holes 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 70 ft. to 80 ft., From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 66.5 ft. to 80 ft., From ft. to ft., From ft. to ft.

GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout intervals: (3) 62 ft. to 66.5 ft., From (3) Bent Grout 10 ft. to 62 ft., From 0 ft. to 10 ft.

What is the nearest source of possible contamination: (NONE)
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Silty clay			
3	10	SAND, silty w/ clay seams			
10	22	SAND, silty w/ intervals of WPP GRAVEL SAND			
22	23	Weathered SILTSTONE			
23	80	SILTSTONE, firm			

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/10/02 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 555 This Water Well Record was completed on (mo/day/yr) 6-3-02
 under the business name of A.W. Pool, Inc. by (signature) Keith Pool