WATER WELL RECORD	Form WWC-5	Division of Wat	er Resources; App. No.∟		
1 LOCATION OF WATER WELL:	Fraction		Township Number		
County: Harper Distance and direction from nearest town of	NE 14 NW 1/4 NE 1/4	13	T31 S	R 9 E/W	
Distance and direction from nearest town of	or city street address of well if	Global Positioning Systems (decimal degrees, min. of 4 digits)			
74N. + 1ky W. of AH	tica K<	Latitude:			
74N. 4 14W. 04 AM	rea, no				
2 WATER WELL OWNER: Gene (RR#, St. Address, Box # : 318 W	oracis 1 00 J				
City, State, ZIP Code : 14	LZNA	Datum:			
marpe	r, KS 67058	Data Collection			
3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL					
LOCATION					
WITH AN "X" IN SECTION BOX: Depth(s) Groundwater Encountered (1)28ft. (2)ft. (3)ft. WELL'S STATIC WATER LEVEL28ft. below land surface measured on mo/day/yr					
SECTION BOX: WELL'S STATIC	N Pump test data: Well water was ft after hours numping gpm				
Pump test data: Well water wasft. after					
WELL WATER TO BE LICED AC. 5 Public motor mumber 0 Air and distance 11 Injection well					
[NW					
W E Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes No					
Sample was submitted					
S			• •		
5 TYPE OF CASING USED: 5 Wrou	ght Iron 8 Concrete til	CASIN	G IOINTS: Glued 2	Clamped	
1 Steel 3 RMP (SR) 6 Asbes	stos-Cement 9 Other (speci			·····	
2 PVC 4 ABS 7 Fiberglass Threaded					
Casing height above land surface 24 in Weight lbs/ft Wall thickness or guage No. 160.051					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify)					
2 Brass 4 Galvanized Steal 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS A					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From					
From					
GRAVEL PACK INTERVALS: Fro	om 20 ft. to	2 ft., From	it. to	. 0 4	
From					
6 GROUT MATERIAL: 1 Neat cement	2 Cement grout 3 Bentonite	4 Other			
6 GROUT MATERIAL: 1 Neat cement Grout Intervals: From	20 ft., From33.	ft. to . 3.5	ft., From	ft. toft.	
What is the nearest source of possible contam	ination:		,		
		stock pens 13 In	secticide Storage	16 Other (specify	
2 Sewer lines 5 Cess pool	8 Sewage lagoon 11 Fuel	storage 14 A	bandoned water well	below)	
			11 11 011 500		
Direction from well?	How m	any feet? 3.0	0		
FROM TO LITHOLO		M TO	PLUGGING INTI	ERVALS	
0 3 Soil.					
3 4 Sand 4 11 Brown Clas					
4 11 Brown Clas	/				
11 17 Dirty Sand					
17 33 Sand 33 34 Grey Clay					
33 34 Grey Clay					
34 52 Sand					
52 60 Fine sand					
60 71 Sand					
71 82 Red Shale			- 24		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed. (2) reconstructed, or (3) plugged					
under my jurisdiction and was completed on (mo/day/year)					
				2-1-08	
under the business name of	s Inc	by (signature)	lan ry	Mh	
INSTRUCTIONS: Use typewriter or ball point pen. I	PLEASE PRESS FIRMLY and PRINT cl	early. Please fill in bland	s, underline or circle the co	orrect answers. Send top	
three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us a					
http://www.kdheks.gov/waterwell/index.html.	,				