

1 LOCATION OF WATER WELL: County: <u>SUMNER</u>	Fraction <u>SW</u> $\frac{1}{4}$ <u>SW</u> $\frac{1}{4}$ <u>NE</u> $\frac{1}{4}$	Section Number <u>23</u>	Township Number <u>T 32</u> S	Range Number <u>R 1</u> EW <u>0</u>
--	---	-----------------------------	----------------------------------	--

Distance and direction from nearest town or city street address of well if located within city?

NECE Botkin + Railroad Tracks, Wellington

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :	<u>Sumner County</u> <u>206 E. Botkin</u> <u>Wellington, KS 67152</u>	Board of Agriculture, Division of Water Resources Application Number:
---	---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>20</u> ft. ELEVATION: <u>1187.89</u>
--	--

Depth(s) Groundwater Encountered 1. 8 ft. 2. 8.15 ft. 3. 7-13-95 ft.

WELL'S STATIC WATER LEVEL 1177.79 ft. below land surface measured on mo/day/yr

Pump test data: Well water was N/A ft. after hours pumping gpm

Est. Yield 8 gpm Well water was 20 ft. after hours pumping gpm

Bore Hole Diameter 8 in. to 20 ft. and in. to ft.

WELL WATER TO BE USED AS:

1 Domestic	3 Feedlot	6 Oil field water supply	8 Air conditioning	11 Injection well
2 Irrigation	4 Industrial	7 Lawn and garden only	9 Dewatering	12 Other (Specify below)

Monitoring well MW-3

Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u> </u> Clamped <u> </u>
------------------------------	----------------	-----------------	--

1 Steel

2 PVC

Blank casing diameter 2 in. to 10 ft. Dia in. to ft. Dia in. to ft.

Casing height above land surface Flush in. weight lbs./ft. Wall thickness or gauge No. 40

3 RMP (SR)

4 ABS

7 Fiberglass

8 RMP (SR)

9 ABS

10 Asbestos-cement

11 Other (specify)

12 None used (open hole)

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel

2 Brass

3 Stainless steel

4 Galvanized steel

5 Fiberglass

6 Concrete tile

7 Gauzed wrapped

8 Wire wrapped

9 Torch cut

10 Other (specify)

11 None (open hole)

12 Drilled holes

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot

2 Louvered shutter

3 Mill slot

4 Key punched

SCREEN-PERFORATED INTERVALS: From 10 ft. to 20 ft. From ft. to ft. From ft. to ft. From ft. to ft.

GRAVEL PACK INTERVALS: From 8 ft. to 20 ft. From ft. to ft. From ft. to ft. From ft. to ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
-------------------	---------------	----------------	-------------	---------

Grout Intervals: From 1 ft. to 8 ft. From ft. to ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? SW How many feet? 320

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>10.5</u>	<u>Silty clay; tr sand</u>			
<u>10.5</u>	<u>20</u>	<u>Clay; sand + gravel</u>			
		<u>reams 15' to base</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>7-6-95</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>571</u> This Water Well Record was completed on (mo/day/yr) <u>11-2-95</u> under the business name of <u>BDAT</u> by (signature) <u>Boyd</u>
