

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SUMNER		NE 1/4 NE 1/4 SW 1/4	23	T 32 S	R 1 E 10
Distance and direction from nearest town or city street address of well if located within city? 206 Botkin, Wellington, KS 67152					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Application Number:			
City, State, ZIP Code :		same as above			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 19.5 ft. ELEVATION: 1191.81			
		Depth(s) Groundwater Encountered 1. 13 ft. 2. 12.94 ft. 3. 12.94 ft.			
		WELL'S STATIC WATER LEVEL 1178.87 ft. below land surface measured on mo/day/yr 7-13-95			
		Pump test data: Well water was N/A ft. after 19.5 hours pumping gpm			
		Est. Yield gpm Well water was N/A ft. after 19.5 hours pumping gpm			
		Bore Hole Diameter 8 in. to 19.5 ft. and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well UMW-6			
		Was a chemical/bacteriological sample submitted to Department? Yes ☐ No ☒ If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes ☐ No ☒			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ☐ Clamped ☐ 2 PVC ☒ 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded ☐ Blank casing diameter 2 in. to 9.5 ft. Dia in. to ft. Dia in. to ft. Casing height above land surface Flush in. weight 40 lbs./ft. Wall thickness or gauge No. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) ☐ 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot ☒ Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From 9.5 ft. to 19.5 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 7 ft. to 19.5 ft. From ft. to ft. From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 7 ft. to ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? W How many feet? 30					
FROM		TO		LITHOLOGIC LOG	
FROM		TO		PLUGGING INTERVALS	
0		1.5		Silty Clay FILL	
1.5		16		Sand FILL	
16		17.5		Silt w/ clay	
17.5		19.5		Sand w/ clay + gravel	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, ☐ reconstructed, or ☐ plugged under my jurisdiction and was completed on (mo/day/year) 2-22-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 571 This Water Well Record was completed on (mo/day/yr) 11-3-95 under the business name of BDAT by (signature) Byrd					