

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SUMNER		NE 1/4 NE 1/4 SW 1/4	23	T 32 S	R 1 E (W)
Distance and direction from nearest town or city street address of well if located within city? 206 E. Botkin, Wellington					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Application Number:			
City, State, ZIP Code :		Wellington, KS 67152			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 18 ft. ELEVATION: 1191.03			
		Depth(s) Groundwater Encountered 1. 13.5 ft. 2. 13.22 ft. 3. 13.22 ft.			
		WELL'S STATIC WATER LEVEL 1177.87 ft. below land surface measured on mo/day/yr 7-13-95			
		Pump test data: Well water was N/A ft. after 18 hours pumping gpm			
		Est. Yield 8 gpm Well water was N/A ft. after 18 hours pumping gpm			
Bore Hole Diameter 8 in. to 18 ft., and 18 in. to 18 ft.		WELL WATER TO BE USED AS:			
1 Domestic		3 Feedlot	6 Oil field water supply	9 Dewatering	11 Injection well
2 Irrigation		4 Industrial	7 Lawn and garden only	10 Monitoring well	12 Other (Specify below)
Was a chemical/bacteriological sample submitted to Department? Yes ✓ No ✓		If yes, mo/day/yr sample was submitted UMW-3			
Water Well Disinfected? Yes NO					
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued NO Clamped NO			
1 Steel		3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded NO
2 PVC		4 ABS	7 Fiberglass		Threaded NO
Blank casing diameter 2 in. to 8 ft., Dia 2 in. to 8 ft., Dia 2 in. to 8 ft.		Casing height above land surface Flush in., weight 40 lbs./ft. Wall thickness or gauge No. 40			
TYPE OF SCREEN OR PERFORATION MATERIAL:		10 Asbestos-cement			
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:		8 Saw cut			
1 Continuous slot		3 Mill slot	6 Wire wrapped	9 Drilled holes	11 None (open hole)
2 Louvered shutter		4 Key punched	7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS:		From 8 ft. to 18 ft.			
GRAVEL PACK INTERVALS:		From 6 ft. to 18 ft.			
6 GROUT MATERIAL:		3 Bentonite			
1 Neat cement		2 Cement grout	4 Other		
Grout Intervals: From 1 ft. to 6 ft.		From 6 ft. to 18 ft.			
What is the nearest source of possible contamination:		10 Livestock pens			
1 Septic tank		4 Lateral lines	7 Pit privy	11 Fuel storage	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	13 Insecticide storage	16 Other (specify below)
Direction from well? SE		How many feet? 50			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	6	Silty Clay; trace coarse sand			
6	18	SILT with clay; trace sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-22-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 571 This Water Well Record was completed on (mo/day/yr) 11-2-95 under the business name of BDAT by (signature) Byl Ethel					