

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number			
County: SUMNER		NE 1/4 NE 1/4 SW 1/4		23		T 32 S		R 1 E/W			
Distance and direction from nearest town or city street address of well if located within city? 206 E. Botkin, Wellington 67152											
2 WATER WELL OWNER: Sumner Co.											
RR#, St. Address, Box # : Same											
City, State, ZIP Code : Same											
Board of Agriculture, Division of Water Resources											
Application Number: 1192.64											
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 18 ft. ELEVATION: 1192.64									
		Depth(s) Groundwater Encountered 1. 14 ft. 2. 13.82 ft. 3. 7-13-95 ft.									
		WELL'S STATIC WATER LEVEL 1178.82 ft. below land surface measured on mo/day/yr 7-13-95									
		Pump test data: Well water was N/A ft. after 18 hours pumping gpm									
		Est. Yield 8 gpm: Well water was 18 ft. after 18 hours pumping gpm									
Bore Hole Diameter 8 in. to 18 ft. and 18 in. to 18 ft.											
WELL WATER TO BE USED AS:											
1 Domestic 3 Feedlot 6 Oil field water supply 8 Air conditioning 11 Injection well											
2 Irrigation 4 Industrial 7 Lawn and garden only ☒ Monitoring well UMW-2											
Was a chemical/bacteriological sample submitted to Department? Yes ☒ No ☒ If yes, mo/day/yr sample was submitted 40											
Water Well Disinfected? Yes ☒ No ☒											
5 TYPE OF BLANK CASING USED:											
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ☒ Clamped ☒											
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded ☒											
Blank casing diameter 2 in. to 8 ft. Dia 8 in. to 18 ft. Dia 18 in. to 40 ft.											
Casing height above land surface Flush in., weight 40 lbs./ft. Wall thickness or gauge No. 40											
TYPE OF SCREEN OR PERFORATION MATERIAL:											
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement											
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) UMW-2											
12 None used (open hole)											
SCREEN OR PERFORATION OPENINGS ARE:											
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)											
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes											
7 Torch cut 10 Other (specify) UMW-2											
SCREEN-PERFORATED INTERVALS: From 8 ft. to 18 ft. From 18 ft. to 18 ft.											
GRAVEL PACK INTERVALS: From 6 ft. to 18 ft. From 18 ft. to 18 ft.											
6 GROUT MATERIAL:											
1 Neat cement 2 Cement grout 3 Bentonite 4 Other UMW-2											
Grout Intervals: From 1 ft. to 6 ft. From 6 ft. to 18 ft. From 18 ft. to 18 ft.											
What is the nearest source of possible contamination:											
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well											
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well											
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)											
13 Insecticide storage 35											
Direction from well? SW How many feet? 35											
FROM		TO		LITHOLOGIC LOG		FROM		TO		PLUGGING INTERVALS	
0		6		Silty clay							
6		17.5		Silt with clay; tr sandy zones							
17.5		18		Sandy clay with silt; tr gravel							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, ☐ reconstructed, or ☐ plugged under my jurisdiction and was completed on (mo/day/year) 2-22-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 571 This Water Well Record was completed on (mo/day/yr) 11-2-95 under the business name of BDAT by (signature) By [Signature]											