

1 LOCATION OF WATER WELL: Fraction SW 1/4 SE 1/4 NW 1/4 Section Number 14 Township Number T 32 S Range Number R 1 EW

County: Sumner Distance and direction from nearest town or city street address of well if located within city? 323 North Washington

2 WATER WELL OWNER: Federal Title RR#, St. Address, Box #: 323 North Washington City, State, ZIP Code: Wellington, KS 67152 Board of Agriculture, Division of Water Resources Application Number: MW4

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with 'X' in the center section]

4 DEPTH OF COMPLETED WELL: 25 ft. ELEVATION: 16-83 ft. Depth(s) Groundwater Encountered: 16-83 ft. WELL'S STATIC WATER LEVEL: 16-83 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 16-83 ft. after 16-83 hours pumping 16-83 gpm Est. Yield 16-83 gpm: Well water was 16-83 ft. after 16-83 hours pumping 16-83 gpm Bore Hole Diameter: 8 in. to 25 ft. and 16-83 in. to 16-83 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded

Blank casing diameter 2 in. to 5 ft. Dia. 16-83 in. to 16-83 ft. Dia. 16-83 in. to 16-83 ft. Dia. Casing height above land surface 16-83 in. weight 16-83 lbs./ft. Wall thickness or gauge No. 16-83

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 25 ft. to 5 ft. From 16-83 ft. to 16-83 ft. From 16-83 ft. to 16-83 ft. From 16-83 ft. to 16-83 ft.

GRAVEL PACK INTERVALS: From 25 ft. to 4 ft. From 16-83 ft. to 16-83 ft. From 16-83 ft. to 16-83 ft. From 16-83 ft. to 16-83 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 4 ft. to 16-83 ft. From 16-83 ft. to 16-83 ft. From 16-83 ft. to 16-83 ft. From 16-83 ft. to 16-83 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage

Direction from well? Southwest How many feet? 60

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

4' 25' Silty clay

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-17-90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 634 This Water Well Record was completed on (mo/day/yr) 7-2-90 under the business name of Shirley E. Testa by (signature) Shirley E. Testa

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

 $\frac{1}{2}$