

1 LOCATION OF WATER WELL: County: Sumner Fraction: SW 1/4 SE 1/4 NW 1/4 Section Number: 14 Township Number: T 32 S Range Number: R 1 EW

Distance and direction from nearest town or city street address of well if located within city: Parking Lot at 313 North Washington, Wellington, KS

2 WATER WELL OWNER: Federal Tire RR#, St. Address, Box #: 323 North Washington City, State, ZIP Code: Wellington, KS 67152 Board of Agriculture, Division of Water Resources Application Number: W106

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with 'X' in the center section]

4 DEPTH OF COMPLETED WELL: 25 ft. ELEVATION: 17.84 ft. WELL'S STATIC WATER LEVEL: 17.84 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 17.84 ft. after 17.84 hours pumping 17.84 gpm

Est. Yield 17.84 gpm: Well water was 17.84 ft. after 17.84 hours pumping 17.84 gpm

Bore Hole Diameter: 8 in. to 25 ft. and 25 in. to 25 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 Brass 4 Galvanized steel 6 Asbestos-Cement 9 Other (specify below) Welded Threaded 3 PVC 4 ABS 7 Fiberglass

Blank casing diameter 2 in. to 5 ft. Dia. 2 in. to 5 ft. Dia. 2 in. to 5 ft. Dia.

Casing height above land surface: Flush in. weight lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 25 ft. to 5 ft. From 25 ft. to 5 ft. From 25 ft. to 5 ft.

GRAVEL PACK INTERVALS: From 25 ft. to 5 ft. From 25 ft. to 5 ft. From 25 ft. to 5 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 4 ft. to 1 ft. From 4 ft. to 1 ft. From 4 ft. to 1 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage

Direction from well? North How many feet? 50

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-17-98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 634 This Water Well Record was completed on (mo/day/yr) 7-2-98 under the business name of Shirley E. Ewing by (signature) M. Shimp

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.