		R WELL RECORD FO		KSA 82a-12			
LOCATION OF WATER WELL:	Fraction	ANA SE		tion Number	Township Number		
ounty: Sumner istance and direction from nearest	NW 1/4	NW ½ SE		15	т 32	S R 1	V
istance and direction from flearest	own or city street add	1022 W. 8 th , W	/ellington,	Ks			
WATER WELL OWNER: Rand	dy Crouch						
R#, St. Address, Box # : 415	W. Lincoln Ave				Board of Agricultur	e, Division of Water Resour	ces
ity State ZIP Code Well	inaton.Ks 671:	52			Application Numbe	er:	
LOCATE WELL'S LOCATON WIT	ΓΗ ₄		25				
AN "X" IN SECTION BOX:	DEPTH OF CO	OMPLETED WELL	ან 	tt. ELEV	ATION:		
	Depth(s) Groundy	vater Encountered 11.5		, II.	2	. II. 3	- Ft
NN						o/day/yr 07/16/07	
†						ours pumpingG	
XiwNE	Est. Yield	Gpm: Well water	was	Ft	. after	lours pumping	pm
	Bore Hole Diamet	er 8.625 In to	J:)	Ft. and	in. to	₋ Ft
M M	1 Domestic	3 Feed lot 6 O	il field water	apply supply	9 Dewatering	12 Other (Specify belo	w)
	2 Irrigation	4 Industrial 7 L	awn and nard	ten (domestic	10 Monitoring well	11 Injection well 12 Other (Specify belo MW-2R	,
SW SE						If yes, mo/day/yr sample wa	
		acteriological sample s	ubililited to t		er Well Disinfected?		20
E TURE OF DIANK SOUNG LIGHT	Submitted	5 Wrought Iron	9 Conor			Glued Clamped	
5 TYPE OF BLANK CASING USED						Welded	
r	P (SR)	6 Asbestos-Cement	9 Other	(specify below	"		
2 PVC 4 ABS	}	7 Fiberglass				Threaded X	
Blank casing diameter 2	in. to 20	Ft., Dia	ln. t	to	ft., Dia	in. to	ft.
Casing height above land surface	FLUSH	n., weight S	CH 40			ge No.	
TYPE OF SCREEN OR PERFORAT		,	7	PVC	10 Asbestos	-cement	
= .	inless steel	5 Fiberglass	8	RMP (SR)	11 Other (sp	ecify)	
, 5.55.	vanized steel	6 Concrete tile	9	ABS	12 None use	ed (open hole)	
CREEN OR PERFORATION OPEN	IINGS ARE:	5 Gauze	ed wrapped			11 None (open hole	;)
1 Continuous slot	3 Mill slot	6 Wire	wrapped		9 Drilled holes		
2 Louvered shutter	4 Key punched	7 Torch			10 Other (specify)		
SCREEN-PERFORATED INTERVAL	_S: From	20 ft. to	35			ft. to	
	From	ft. to		ft. Fi	om	ft. to	_ Ft
SAND PACK INTERVALS:	From	19 ft. to	35	ft. Fr	om	ft. to	₋ Ft
	From	ft. to		ft. Fr	om	ft. to	Ft
GROUT MATERIAL: 1 Ne	at cement 2	Cement grout	3 Ben	tonite	4 Other		
Grout Intervals From3 0	a	Ft	7 ft.	19			
		FIOINZ	to	10 Livesto		ft. to 4 Abandoned water well	- H.
What is the nearest source of possible	4 Lateral lines	7 Pit privy		11 Fuels	•	5 Oil well/ Gas well	
1 Septic tank		8 Sewage		12 Fertiliz	-	6 Other (specify below)	
2 Sewer lines	5 Cess pool	_	_		cide storage	Contaminated Site	
3 Watertight sewer lines	6 Seepage pit	9 Feedyar	u	How many f	•	Containmated Site	-
Direction from well? FROM TO CODE	LITHOLO	OGIC LOG	FROM	TO		NG INTERVALS	
	Concrete	0010 1000	TION		1 20001	INO INTERVALO	
.5 13	Silty Clay (CL) r	ed brown				-	
	Clayey Sand						_
	Sand (SW) fine t	to medium					
34 35 5	Shale						
	nd of Borehole)					
			-				
				+			
				+	THE STATE OF THE S		
				+ +			
	-1	·					
7 CONTRACTOR'S OR LANDOWN	IER'S CERTIFICATIO	N: This water well wa	s (x) construc	cted, (2) recor	structed, or (3) plugge	ed under my jurisdiction and	w
	07/10					owledge and belief. Kansa	
Vater Well Contractor's License No.		585				n (mo/day/yr) 08/06/0	
nder the business name of		d Environmenta			(signature) Bradle		
INSTRUCTIONS: Please fill in bla	inks and circle the corre	ct answers. Send three o	opies to Kans	as Department	of Health and Environme	ent, greau of Water, Topeka,	
Kansas 66620-0001 Telephone:	040 000 EE4E Camalas	MATED MELL OWN	ARTO And asket	fac	opordo`		