				Form WWC-5				
LOCATION OF V		Fraction SW	397 11	Sec	tion/Number	غ دا		Range Number
ounty: Sum	nerest town	or city street address	of well if locate	d within city?	HELLI	y - 3	2 (S/I	R / E(W)
nstance and direc	ion nom nearest town to	9 E. Ho		17.	1.5	1/<		
WATER WELL	OWNED: THE P	Ferguson	crey, 1	Ne lling	10/1			
WATER WELL		Harvey		•		D	.f. A surfacella cons. Di	delen of Makey Descripes
RR#, St. Address,	4.3 4		1 140	57)				vision of Water Resource
City, State, ZIP Co	S LOCATION WITH 4		S COLL	66	4 ELEVA		tion Number:	22
AN "X" IN SECT	ION BOX:	epth(s) Groundwater	Encountered 1		ft. :	2	ft. 3.	ft.
NW -	_	Pump test	data: Well wate	er was	ft. a	ifter	hours pum	ping gpm ping gpm
w i	Bo	ore Hole Diameter	7.18in. to		ft.,	and	in. 1	o
E " !	i w	ELL WATER TO BE	USED AS:	5 Public water	r supply	8 Air condition	ing 11 In	jection well
-		1 Domestic		6 Oil field war		9 Dewatering		ther (Specify below)
3 -	3 3	2 Irrigation	4 Industrial	DLawn and g	arden only	10 Monitoring v	vell ,	
i_	ı w	as a chemical/bacteri	iological sample s	submitted to De	•		•	no/day/yr sample was sub
	\$ mi	itted			Wa		cted? Yes 🗡	
TYPE OF BLAN	K CASING USED:	5 W	rought iron	8 Concre	ete tile	CASING	JOINTS: Glued	X Clamped
1 Steel	3 RMP (SR)	6 As	sbestos-Cement	9 Other	(specify below	w)	Welded	1
[≥ / PVC	4 ABS	7 Fil	berglass				Thread	ed
Blank casing diame	eter $oldsymbol{5}$ in.	to 35	ft., Dia	in. to		ft., Dia	in	. to ft.
Casing height abov	e land surface	. / . % in., w	veight /.6.0	0	Ibs.	ft. Wall thickne	ss or gauge No.	
TYPE OF SCREEN	OR PERFORATION N	MATERIAL:			С	10 /	Asbestos-cemen	t
1 Steel	3 Stainless st	teel 5 Fil	berglass	8 RM	IP (SR)	11 (Other (specify) .	
2 Brass	4 Galvanized	steel 6 Cd	oncrete tile	9 AB	S	12	None used (oper	n hole)
CREEN OR PER	FORATION OPENINGS	S ARE:	5 Gauze	ed wrapped		8 Saw cut		11 None (open hole)
1 Continuous	slot 3 Mill s	slot	6 Wire	wrapped		9 Drilled hole	es	
2 Louvered s	hutter 4 Key	punched	7 Torch	cut		10 Other (spe	cify)	
SCREEN-PERFOR	ATED INTERVALS:	From	ft. to	<i>5</i> 5	ft., Fro	m	ft. to .	
		From						
GRAVEL	PACK INTERVALS:							
		From	ft. to		ft., Fro		ft. to	ft.
GROUT MATER	NAL: 1 Neat cerr	nent 2Cer	ment grout	3 Bento	nite 4		-	
Grout Intervals:	From ft		ft., From	3.3 ft.	to 35.	ft., From		ft. to
What is the neares	t source of possible cor				_	stock pens		indoned water well
1 Septic tank	•		7 Pit privy		11 Fuel storage 15 Oil well/Gas w			well/Gas well
2 Sewer lines 5 Cess pool			8 Sewage lagoon		12 Fertilizer storage		16 Other (specify below)	
3 Watertight	sewer lines 6 Seepage		9 Feedyard			cticide storage	Evan	t Know
Direction from well		- р	o i oodyala		How ma	•		- y
FROM TO		LITHOLOGIC LOG		FROM	TO	iny leet:	PLUGGING IN	TERVALS
0 19	501/ Y	+Clay						
0 19	Tight -	Shold						
11 32	19m	21,41						
			V- VIII					
								<u> </u>
					L			
CONTRACTOR	S OR LANDOWNER'S	CERTIFICATION: T	his water well w	as (1) constru	cted, (2) reco	onstructed, or (3	B) plugged under	my jurisdiction and was
completed on (mo/d	day/year) 5 - /	5~9/						ledge and belief. Kansas
Nater Well Contrac	tor's License No	596	. This Water W	ell Record wa	s completed	on (mo/day/yr)	6-16	771
inder the business	name of Metz	Dater Well 5			by (signa		annia	mot
	se typewriter or ball point pen.	. PLEASE PRESS FIRMLY	and PRINT clearly. Pl	ease fill in blanks.			s. Send top three co	pies to Kansa Department
mornochona: C		peka, Kansas 66620-7320.						Department