

1 LOCATION OF WATER WELL: Fraction 1/4 NE 1/4 NW 1/4 Section Number 15 Township Number T 32 S Range Number R 1 EW

County: SUMNER NE NE NW 1/4 15 T 32 S R 1 EW

Distance and direction from nearest town or city street address of well if located within city?

See Below -

2 WATER WELL OWNER: Bill Oathout 1416 No. Plum WELLINGTON KS 67152 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION: 17 ft. below land surface measured on mo/day/yr 5-2-91

Depth(s) Groundwater Encountered 1. 17 ft. 2. 19 ft. 3. 20 ft.

WELL'S STATIC WATER LEVEL 17 ft. below land surface measured on mo/day/yr 5-2-91

Pump test data: Well water was 19 ft. after 2 hours pumping 20 gpm

Est. Yield 20 gpm: Well water was 19 ft. after 2 hours pumping 20 gpm

Bore Hole Diameter 11 in. to 60 ft. and in. to

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped

2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded

Blank casing diameter 5 in. to 17 ft. Dia. in. to lbs./ft. Wall thickness or gauge No. 160 PWT

Casing height above land surface 12 in. weight 2.60

TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes

2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 17 ft. to 60 ft. From ft. to ft.

GRAVEL PACK INTERVALS: From 17 ft. to 60 ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 17 ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well

1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage

Direction from well? South How many feet? 80

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 2 Top soi /

2 10 Clay

10 18 SAND

18 60 Cherokee / shale

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-2-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 5-2-91 under the business name of Weninger & Son (signature)

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.