


1 LOCATION OF WATER WELL: Fraction NW 1/4 NE 1/4 NE 1/4 Section Number 1 Township Number T 32 S Range Number R 10 EW

County: Barber  
 Distance and direction from nearest town or city street address of well if located within city?  
4 E 3 N Sharon

2 WATER WELL OWNER: Vernon McDaniel  
 RR#, St. Address, Box #: attica, KS 67009  
 City, State, ZIP Code: attica, KS 67009  
 Board of Agriculture, Division of Water Resources  
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
  
 4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION: 40 ft.  
 Depth(s) Groundwater Encountered 1. 1 ft. 2. 40 ft. 3. 40 ft.  
 WELL'S STATIC WATER LEVEL: 10 ft. below land surface measured on mo/day/yr  
 Pump test data: Well water was 10 ft. after 8 hours pumping 10 gpm  
 Est. Yield 10 gpm: Well water was 60 ft. after 8 hours pumping 10 gpm  
 Bore Hole Diameter: 8 in. to 60 ft., and 8 in. to 60 ft.  
 WELL WATER TO BE USED AS:  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well  
 Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped  
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded  
 7 Fiberglass Threaded  
 Blank casing diameter 4 in. to 40 ft., Dia. 40 in. to 40 ft., Dia. 40 in. to 40 ft.  
 Casing height above land surface 240 in., weight 173 lbs./ft. Wall thickness or gauge No. 173  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)  
 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify)  
 SCREEN-PERFORATED INTERVALS: From 40 ft. to 60 ft., From 40 ft. to 60 ft.  
 GRAVEL PACK INTERVALS: From 10 ft. to 60 ft., From 10 ft. to 60 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grout Intervals: From 0 ft. to 10 ft., From 10 ft. to 10 ft., From 10 ft. to 10 ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage  
 Direction from well? 5 How many feet? 2000

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
<u>3</u>	<u>30</u>	<u>Soil</u>			
<u>30</u>	<u>60</u>	<u>Shale</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-24-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 3-14-83 This Water Well Record was completed on (mo/day/yr) 3-14-83 under the business name of Lyman Bros by (signature) Richard Lyman

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY T 32 R 10 EW SEC. 1 NW 1/4 NE 1/4 NE 1/4