## WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

I	County	Fraction	Section	number	Township number	Range number
1. Location of well:	Barber	NE 1/4 NW1/4 SE	1/4	5	т <b>32</b> s	R 12 W E/W
2. Distance and direct	tion from nearest town or city: 3		3. Owner of we	II: Cha	arles Clarke	
Street address of well location if in city: MEDICINE LODGE, KS R.R. or street:  City, state, zip code: Medicine Lodge, Kansas						
4. Locate with "X" in section below:  Sketch map:					6. Bore hole dia. 30 in. Completion date Well depth 60 ft. 18 July 19	
ī [ ; ] ; ]					7 Cable tool Rotary Driven Dug	
					Hollow rod Jetted Bored X Reverse rotary  8. Use: Domestic Public supply Industry	
E X WELL					X Irrigation Air conditioning Stock	
					Lawn Oil field water Other  9. Casing: Material theight Above or below	
<u>                                     </u>					Threaded Welded!Surface12in.	
DROINAGE DROINAGE					RMPPVCWeight_32.7_lbs./ft. Dia 16 in. to 16 ft. depth Wall Thickness: inches or	
5. Type and color of n		erse F=fine	From	То	Dia in. to ft. der	oth gage No
Sandy soil				2	10. Screen: Manufacturer's	.,,,,
Danay 50.	A-L		0	-	Slot/gauze YR	≥ Dia
Clay, sandy				10	Set betweenft. andft.	
Sand, fine to coarse				20	Gravel pack? 155 Size range of material 16 3 3	
Clay, brown and sandy				26	11. Static water level: mo./day/yrft. below land surface Date 18 July 79	
Sand, fine to coarse and fine gravel, very silty				46	12. Pumping level below lan	d surfaces: hrs. pumping 500 g.p.m.
Sand, fine to coarse and coarse gravel, loose				60_	29 ft. after 1 hrs. pumping 700 g.p.m.  Estimated maximum yield g.p.m.	
Shale, red				65	13. Water sample submitted:	_ ' ''
					Yes No  14. Well head completion:	Date
					Pitless adapter	12_ Inches above grade
					15. Well grouted? With: Neat cement	★ Bentonite Concrete
					Depth: From ft. to	
				-	16. Nearest source of possib	Type <b>WONES</b>
	,			ļ <u>.</u>	Well disinfected upon compl	Not installed
					Manufacturer's name 50	MONS
					Model number 500 100 Length of drop pipe 40	HP Volts ft. capacity <b>600</b> g.p.m.
					Type: Submersible	X Turbine
	<i>n</i>	h!		<u> </u>	Jet	Reciprocating
18. Elevation:	(Use a second s			1	Centrifugal  20. Water well contractor's	Other
5'XID'XR" Slat					This well was drilled under n	ny jurisdiction and this report
Topography:					is true to the best of my know	wledge and belief.
Topography:  - Hill Slope  Slope  Six 10' x 8" Slat  Faund at Sinyland					Business name Address Sex 103	2 PRATTIKS No.
Upland	V	`			Signed Authorized re	Date See
Valley Valley	e and pink copies to the Department	further of the second			Authorized re	Form WWC-5