

1 LOCATION OF WATER WELL: Fraction SE 1/4 SE 1/4 NW 1/4 Section Number 12 Township Number T 32 S Range Number R 12 EW

Distance and direction from nearest town or city street address of well if located within city?
414 S Main Medicine Lodge, KS

2 WATER WELL OWNER: Jerry Bryan
RR#, St. Address, Box #: 414 S Main Board of Agriculture, Division of Water Resources
City, State, ZIP Code: Medicine Lodge, KS 67104 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-acre section with an 'X' in the center, labeled with cardinal directions N, S, E, W and sub-sections NW, NE, SW, SE. A vertical scale bar indicates 1 mile.]

4 DEPTH OF COMPLETED WELL: 15.0' ft. ELEVATION: N.A.
Depth(s) Groundwater Encountered: 1.9' ft. 2. ft. 3. ft.
WELL'S STATIC WATER LEVEL: N.A. ft. below land surface measured on mo/day/yr
Pump test data: Well water was ft. after hours pumping gpm
Est. Yield gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter: 8" in. to ft. and in. to ft.
WELL WATER TO BE USED AS:
5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
Blank casing diameter: 2" in. to ft. Dia. in. to ft. Dia. in. to ft.
Casing height above land surface: Flush in. weight: .703 lbs./ft. Wall thickness or gauge No. 154
TYPE OF SCREEN OR PERFORATION MATERIAL:
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
SCREEN-PERFORATED INTERVALS: From 4.75' ft. to 14.75' ft. From ft. to ft.
GRAVEL PACK INTERVALS: From 3.50' ft. to 14.75' ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 3.50' ft. to 1.0' ft. From ft. to ft. From ft. to ft.
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage
Direction from well? Southwest How many feet? approx 100'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.0'	5.0'	Clay, Fill material.			
5.0'	9.0'	Silty clay with some sand.			
9.0'	15.0'	Silty sandy clay. Some carbon stains.			
Flush mount waiver was granted 4-21-92 for Jerry Service - Medicine Lodge by Don Taylor					

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-4-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 5-20-92 under the business name of Geotechnical Services, Inc. by (signature) Allison Irwin