

1 LOCATION OF WATER WELL: County: Barber Fraction: SW 1/4 SE 1/4 SE 1/4 Section Number: 20 Township Number: T 32 S Range Number: R 15 E

Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: S. T. MARSH Ranch Inc  
 RR#, St. Address, Box #: RR Sun City KS  
 City, State, ZIP Code: RR Sun City KS 137  
 Board of Agriculture, Division of Water Resources  
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N			
---	NW	---	NE
W	---	---	E
---	SW	---	SE
S			

4 DEPTH OF COMPLETED WELL: 137 ft. ELEVATION: \_\_\_\_\_ ft.  
 Depth(s) Groundwater Encountered: \_\_\_\_\_ ft. 2 \_\_\_\_\_ ft. 3 \_\_\_\_\_ ft.  
 WELL'S STATIC WATER LEVEL: 60 ft. below land surface measured on mo/day/yr \_\_\_\_\_ ft.  
 Pump test data: Well water was \_\_\_\_\_ ft. after \_\_\_\_\_ hours pumping \_\_\_\_\_ gpm  
 Est. Yield: 10 gpm Well water was \_\_\_\_\_ ft. after \_\_\_\_\_ hours pumping \_\_\_\_\_ gpm  
 WELL WATER TO BE USED AS:  
 1 Domestic     2 Irrigation     3 Feedlot     4 Industrial  
 5 Public water supply     6 Oil field water supply     7 Domestic (lawn & garden)  
 8 Air conditioning     9 Dewatering     10 Monitoring well  
 11 Injection well     12 Other (Specify below)  
 Was a chemical/bacteriological sample submitted to Department? Yes \_\_\_\_\_ No   
 Water Well Disinfected? Yes  No \_\_\_\_\_

5 TYPE OF BLANK CASING USED:  
 1 Steel     2 PVC     3 RMP (SR)     4 ABS  
 5 Wrought iron     6 Asbestos-Cement     7 Fiberglass  
 8 Concrete tile     9 Other (specify below)  
 CASING JOINTS:  Glued     Clamped     Welded     Threaded  
 Blank casing diameter: 5 in. to 137 ft., Dia \_\_\_\_\_ in. to \_\_\_\_\_ ft., Dia \_\_\_\_\_ in. to \_\_\_\_\_ ft.  
 Casing height above land surface: 12 in., weight: 160 lbs./ft. Wall thickness or gauge No. \_\_\_\_\_  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel     2 Brass     3 Stainless Steel     4 Galvanized Steel  
 5 Fiberglass     7 PVC     8 RMP (SR)     10 Asbestos-Cement  
 6 Concrete tile     9 ABS     11 Other (Specify)     12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot     2 Louvered shutter     3 Mill slot     4 Key punched  
 5 Gauzed wrapped     6 Wire wrapped     7 Torch cut     8 Saw cut     9 Drilled holes     10 Other (specify) \_\_\_\_\_ ft.  
 11 None (open hole)  
 SCREEN-PERFORATED INTERVALS: From 137 ft. to 119 ft., From 99 ft. to 79 ft.  
 GRAVEL PACK INTERVALS: From 137 ft. to 24 ft., From \_\_\_\_\_ ft. to \_\_\_\_\_ ft.

6 GROUT MATERIAL:  1 Neat cement     2 Cement grout     3 Bentonite     4 Other \_\_\_\_\_  
 Grout Intervals: From 24 ft. to 0 ft., From \_\_\_\_\_ ft. to \_\_\_\_\_ ft., From \_\_\_\_\_ ft. to \_\_\_\_\_ ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank     2 Sewer lines     3 Watertight sewer lines  
 4 Lateral lines     5 Cess pool     6 Seepage pit  
 7 Pit privy     8 Sewage lagoon     9 Feedyard  
 10 Livestock pens     11 Fuel storage     12 Fertilizer storage     13 Insecticide storage  
 14 Abandoned water well     15 Oil well/Gas well     16 Other (specify below)  
 Direction from well? \_\_\_\_\_ How many feet? Nothing on location

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Red Sand			
3	5	White Clay			
5	20	Red Clay			
20	40	Fine Sand / Orange			
40	70	Red Clay - gray streaks (Hard)			
70	75	Red Clay / sand streaks			
75	80	Red Clay / Rock streaks			
80	100	Red Clay / sand streaks			
100	105	Red Clay / Very Hard			
105	125	Red Clay / gray streaks			
125	137	Red Slate			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was  constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-10-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 672 This Water Well Record was completed on (mo/day/yr) 3-23-96 under the business name of Crawley Water Well by (signature) [Signature]