

1 LOCATION OF WATER WELL: County: Comanche Fraction NW 1/4 SW 1/4 SW 1/4 Section Number 7 Township Number T 32 S Range Number R 18 EW

Distance and direction from nearest town or city street address of well if located within city? 43 Feet East of Central Street and 105 Feet South of Second Street, Coldwater, KS 01928025 MW-3

2 WATER WELL OWNER: Mr. Vic Kropf RR#, St. Address, Box #: 1215 East 27th Street City, State, ZIP Code: Hutchinson, KS 67501 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 2x2 grid with NW, NE, SW, SE quadrants. An 'X' is marked in the SW quadrant.]

4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION: Approximate Surface Elevation: 2100 ft.

Depth(s) Groundwater Encountered 1. 49.5 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 49.5 ft. below land surface measured on mo/day/yr 08/11/92

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield N/A gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 8.25 in. to ft., and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No X

5 TYPE OF CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued Clamped Welded Threaded X

Blank casing diameter 2 in. to 37.5 ft., Dia. in. to ft., Dia. in. to ft.

Casing height above land surface -3 in., weight lbs./ft. Wall thickness or gauge No. Schedule 40

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)

SCREEN-PERFORATED INTERVALS: From 37.5 ft. to 60 ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 35 ft. to 60 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0 ft. to 33 ft., From 33 ft. to 35 ft., From ft. to ft.

What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)

Direction from well? How many feet?

| FROM | TO | LITHOLOGIC LOG | FROM | TO | PLUGGING INTERVALS |
|------|------|-----------------------------------|------|----|--------------------|
| 0.0 | 0.3 | Asphalt | | | |
| 0.3 | 9.0 | Sandy Fat Clay, Gray-Brown | | | |
| 9.0 | 13.5 | Fat Clay With Sand, Red-Brown | | | |
| 13.5 | 28.5 | Sandy Fat Clay, Gray-Brown, Brown | | | |
| 28.5 | 43.0 | Fat Clay, Trace Sand, Brown | | | |
| 43.0 | 47.0 | Fine to Medium Sand, Brown | | | |
| 47.0 | 60.0 | Fine to Coarse Sand, Brown | | | |

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 08/11/92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 10-5-93 under the business name of Terracon Consultants, Inc. by (signature) Steve Fischer

OFFICE USE ONLY
T
R
EW
SEC.
1/4
1/4
1/4