

1 LOCATION OF WATER WELL:			Fraction	Section Number	Township Number	Range Number
County:	Clark	NW ¼ NE ¼ SE ¼	5	T 32 S	R 21 E	W
Distance and direction from nearest town or city street address of well if located within city? From , appx				Global Positioning System (decimal degrees, min. of 4 digits)		
2 WATER WELL OWNER: Jim Harden RR#, St. Address, Box # : 1321 CR 29 City, State, ZIP Code : Ashland Ks 67831				Latitude: Longitude: Elevation: Datum: Data Collection Method:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 129 ft.				
<div style="text-align: center;">N NW NE W X E SW SE S</div>		Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 8 Air conditioning 11 Injection well 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No x ; If yes, mo/day/ys Sample was submitted Water Well Disinfected? Yes x No				
5 TYPE OF CASING USED:		CASING JOINTS: Glued Clamped Welded X Threaded				
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)						
2 PVC 4 ABS 7 Fiberglass						
Blank casing diameter 16 in. to 129 ft., Dia		in. to ft., Dia in. to ft.				
Casing height above land surface 12 in., Weight 42 lbs./ft.		Wall thickness or gauge No. .250				
TYPE OF SCREEN OR PERFORATION MATERIAL:						
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 9 ABS 11 Other (specify)						
2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:						
1 Continuous slot 3 Mill slot 5 Guaze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)						
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)						
SCREEN-PERFORATED INTERVALS:		From 69 ft. to 109 ft. From ft. to ft. From ft. to ft.				
GRAVEL PACK INTERVALS:		From 20 ft. to 129 ft. From ft. to ft. From ft. to ft.				
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other				
Grout Intervals From 0 ft. to 20 ft. From ft. to ft. From ft. to ft.						
What is the nearest source of possible contamination: none observed						
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify below)						
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well						
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 15 Oil well/ gas well						
Direction from well?		How many feet?				
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	
0	1	Top Soil Sand				
1	6	Sandy clay				
6	11	Fine to med loose				
11	21	Blue clay				
21	26	Sand fine to med w/gravel				
26	35	clay				
35	70	clay				
70	109	Sand fine to med w/gravel				
109	115	Red bed				

