


1 LOCATION OF WATER WELL: Fraction SW 1/4 SW 1/4 NE 1/4 Section Number 11 Township Number T 32 S Range Number R 25 E  
 County: Clark

Distance and direction from nearest town or city street address of well if located within city?  
1 1/2 mi. E and 1/2 mi. S of Meade

2 WATER WELL OWNER: Phil Ridenour  
 RR#, St. Address, Box #: 109 W. Ave 1 Board of Agriculture, Division of Water Resources  
 City, State, ZIP Code: Cimarron, KS 67835 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
  
 4 DEPTH OF COMPLETED WELL: 140 ft. ELEVATION:  
 Depth(s) Groundwater Encountered 1. 76 ft. 2. ? ft. 3. ? ft.  
 WELL'S STATIC WATER LEVEL 76 ft. below land surface measured on mo/day/yr 6-14-93  
 Pump test data: Well water was 10 ft. after 12 hours pumping 30 gpm  
 Est. Yield 4 gpm; Well water was ? ft. after ? hours pumping ? gpm  
 Bore Hole Diameter: 8 3/4 in. to 140 ft., and ? in. to ? ft.  
 WELL WATER TO BE USED AS:  
 Domestic  3 Feedlot  6 Oil field water supply  9 Dewatering  12 Other (Specify below)  
 2 Irrigation  4 Industrial  7 Lawn and garden only  10 Monitoring well  
 Was a chemical/bacteriological sample submitted to Department? Yes ? No ; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes  No

5 TYPE OF BLANK CASING USED:  
 1 Steel  3 RMP (SR)  6 Asbestos-Cement  9 Other (specify below)  Welded  
 PVC  4 ABS  7 Fiberglass  CASING JOINTS: Glued  Clamped  
 Blank casing diameter 5 in. to 100 ft., Dia. ? in. to ? ft., Dia. ? in. to ? ft.  
 Casing height above land surface: 24 in., weight ? lbs./ft. Wall thickness or gauge No. 200 lb.  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  PVC  10 Asbestos-cement  
 1 Steel  3 Stainless steel  5 Fiberglass  8 RMP (SR)  11 Other (specify)  
 2 Brass  4 Galvanized steel  6 Concrete tile  9 ABS  12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot  3 Mill slot  5 Gauzed wrapped  Saw cut  11 None (open hole)  
 2 Louvered shutter  4 Key punched  6 Wire wrapped  9 Drilled holes  
 7 Torch cut  10 Other (specify)  
 SCREEN-PERFORATED INTERVALS: From 100 ft. to 140 ft., From ? ft. to ? ft.  
 GRAVEL PACK INTERVALS: From 20 ft. to 140 ft., From ? ft. to ? ft.

6 GROUT MATERIAL:  1 Neat cement  Cement grout  3 Bentonite  4 Other  
 Grout intervals: From top ft. to 20 ft., From ? ft. to ? ft., From ? ft. to ? ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank  4 Lateral lines  7 Pit privy  10 Livestock pens  Abandoned water well  
 2 Sewer lines  5 Cess pool  8 Sewage lagoon  11 Fuel storage  15 Oil well/Gas well  
 3 Watertight sewer lines  6 Seepage pit  9 Feedyard  12 Fertilizer storage  16 Other (specify below)  
 13 Insecticide storage  
 Direction from well? W How many feet? 15

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	15	limestone			
15	25	brown clay			
25	40	sandy brown clay			
40	82	sand & gravel			
82	100	blue clay			
100	112	sand rock			
112	140	sandy red clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was  constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-14-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 101 This Water Well Record was completed on (mo/day/yr) 6-15-93 under the business name of Bartel Well Drilling, Inc. by (signature) Kenber J. Bartel

OFFICE USE ONLY  
T  
R  
EW  
SEC.  
1/4  
1/4  
1/4