


1 LOCATION OF WATER WELL: Fraction C 1/4 W 1/2 SW 1/4 Section Number 5 Township Number T 32 S Range Number R 26 E
 County: Meade

Distance and direction from nearest town or city street address of well if located within city?
East edge of Meade, Ks at Hwy 54 7E on Hwy 160 1320' N & E into location

2 WATER WELL OWNER: Raydon Exploration Inc. #1-5 St. Lawrence
 RR#, St. Address, Box # : 9400 N Broadway Ext. #400 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : Oklahoma City, Ok 73114 Application Number: 20040841

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL 180 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1 100 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL 180 ft. below land surface measured on mo/day/yr 10-14-04
 Pump test data: Well water was 132 ft. after 1 hours pumping 100 gpm
 Est. Yield 100 gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
 2 PVC 4 ABS 7 Fiberglass Threaded
 Blank casing diameter 6 in. to 180 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface 24 in., weight 4.074 lbs./ft. Wall thickness or guage No. SDR 21.316
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-Cement
 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 Other (Specify)
 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 140 ft. to 180 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 50 ft. to 180 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other hole plug
 Grout Intervals: From 1 ft. to 25 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer line 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? East How many feet? 460

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Surface			
1	80	Clay			
80	100	Sand			
100	135	Sandy clay and clay			
135	173	Sand and gravel			
173	176	Clay "tan yellow blue"			
176	180	Clay "red and blue"			

RECEIVED
 NOV 08 2004
 BUREAU OF WATER

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-14-04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. KWWC-430 This Water Well Record was completed on (mo/day/yr) 10-14-04 under the business name of Howard Drilling Co. Box 806 Beaver, Ok 73932 by (signature) Howard

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.