		SW-SW-SE-NW) EOFM WWC-5	٥٢	
XX7 A TETET	D 33/17/1	LL RECORD Form WWC-5	DF Division of Water Brown Ann Mr.	
		NOF WATER WELL: Fraction	Division of Water Resources App. No. Section Number Township No. Range Number	
Coun	ty: Mea	eade NW ¼ SE ¼ SW ¼ SW	/ ¼ 1 T 32 S R 26 □E ☑W	
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here Dorna Bacon House 31046 N Road, Fowler 15 Global Positioning System (GPS) information: Latitude: .37.17.29.78"				
			<u>Datum</u> : ☐ WGS 84, ☐ NAD 83, ☐ NAD 27	
RR#, Street Address, Box #: R+1 Box US City, State, ZIP Code : Forgan OK 7202C			Collection Method: ☐ GPS unit (Make/Model:) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m	
3 LOCATE WELL WITH AN "X" IN SECTION BOX: N Depth(s) Groundwater Encountered (1)				
WELL WATER TO BE USED AS:				
5 TYPE OF CASING USED: Steel PVC Other				
CASING JOINTS: Glued Clamped Welded Threaded				
Casing diameter .5 in. to .120				
Casing height above land surface. 18 in., Weightlbs./ft., Wall thickness or gauge No200#				
TYPE OF SCREEN OR PERFORATION MATERIAL:				
☐ Steel ☐ Stainless Steel				
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE:				
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole) Louvered shutter Key punched Saw cut Other (specify)				
Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From 129 ft. to 160 ft. From ft. to ft.				
From				
GRAVEL PACK INTERVALS: From 24 ft. to 160 ft., From ft. to ft.				
From				
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☑ Bentonite ☐ Other				
Grout Intervals: From .4				
What is the nearest source of possible contamination:				
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☑ Other (specify below)				
	1 — , , ,			
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well water well Direction from well North East Distance from well 60				
FROM	TO		nce from well	
-		LITHOLOGIC LOG FROM	1 10 LITHO. LOG (cont.) of PLOGGING INTERVALS	
	8 12	topsoil		
12	18	sand brown clay		
18	100	sand and gravel		
	120	sandy brown clay		
120	130	blue clay		
130	140	sand and gravel		
140	160	sand rock and red clay		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged				
under my jurisdiction and was completed on (mo/day/year) .19/22/2019 and this record is true to the best of my knowledge and belief.				
Kansas Water Well Contractor's License No. 101 This Water Well Record was completed on (mo/day/year) 1/10/2011				
under the business name of Bartel Well Drilling, Inc. by (signature) . Kulling L. Bartel				
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white blue risk) to Kassas Department of Health and Environment of Health and H				
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at				
http://www.kdheks.gov/waterwell/index.html.				
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy				