USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

	County	Fraction			Section	number	Townshi	ip number		Rang	ge number		
1. Location of well:	Meade	S. 1/4 11.1	1/4 派孟	1/4	2		т	32	S	R	27	E/W	
2. Distance and direction from nearest town or city:					3. Owner of well: Ross Bros								
5/1/2 east & 74 north of Meage R.R. or street:								Kansas	5				
City, state, zip code:										_			
4. Locate with "X" in section below: Sketch map:						6. Bore hole dia. 28 in. Completion date Well depth 210 ft. 7-39-75							
							7 Cable tool Rotary Driven Dug						
							Hallow rod Jetted Bored Reverse rotary						
							8. Use: Domestic Public supply Industry						
							X Irrigation Air conditioning Stock Lawn Oil field water Other						
sw se							9. Casing: Material Metal Height: Above or below						
1							Threaded Welded X Surface 12 in.						
S 1								RMP PVC Weight 31 - 66 lbs./ft. Dia. 16n. to 210r. depth Wall Thickness: inghes or					
5. Type and color of					From	То	Dia.	in. to f	. dept	h ¦gag	• No. <u>• 1</u>	.88	
	Carrier Co.	With a second						n: Manufactu Brown F			0		
Surface		· •				3		1.7%		Dia	16		
Green and brown clay					2	61	Slot/gauz	\sim	8	Leng	27.0		
½ med. sand and gravel					61	63	Set betwe		ft. a	ft.an nd	u	ft.	
the state of the s					63	86	Gravel p	ack? <u>yes</u> s	ize ran	ge of	material	½ down	
Sandy coleche clay								c water level: ft.below la				mo./day/yr.	
Good sand and gravel (dry)					86	94	-	ing level belo					
Sandy coleche clay					91	101	200	ft. after2	h	rs. pu	mping <u>55</u>		
Good med. sand and gravel					101	113		ft. after		550	mping ——	g.p.m.	
Brown clay with 40% gravel mixed					117	115		r sample submi			,	mo./day/yr.	
					מרר	107	Ye			ate _			
Good med. sand and gravel					115		14. Well head completion: Pitless adapter Inches above grade						
Sandy brown coleche clay					123	146		grouted? No					
Fine sand with 35% clay mixed					146	152	1						
Sandy brown clay					152	160		est source of p			ft.	NA	
1/2 Med, sand and gravel with 20% clay mix				e d	160	165	ft	Directio	n		Туре		
							Well dist	nfected upon c	complet				
prown cra3	with 25 to 30%	rine sand			165	175	17. Pump Manufact	: turer's name _		<u>×</u>	Not installe	ed	
A-1 med. sand and gravel					17	r 193	Model nu						
Yellow clay with rock stringers					193	205	Length of Type:	drop pipe —		_ ft.	capacity —	g.p.m.	
Red shale OA 705 7/m					209	210	S	ubmersi ble			Turb	į.	
	(Use a second s	heet if needed)					c	et entrifugal			Reci	iprocating er	
18. Elevation:	19. Remarks:	·						er well contrac	tor's c	ertific			
2505 ym 10' of grout and pump slab to be installed							This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.						
Topography:												100	
by customer-he knows this is a regulation							Dodge City kanese						
Slope Wayre Ross 2505 Valley							Address -	7-10	7	Zh	ė .	B-28	
Valley		- 1	3?				oigned €	Authorize	ed repr	esento	tive	116	