Ross #5

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

	· · · · · · · · · · · · · · · · · · ·	··						
1 1	County	Fraction		Section	number	Township number	Range number	
1. Location of well:	Me ade	NE 1/4 NE 1/4 NE	1/4	2		T 32 s	R 27 E/W	
2. Distance and direction from negrest town or city: 6 min east & 1 mi north of Meade 3. Owner of Meade					er of well: Ross Bros			
Street address of well location if in city:					. 1	Meade, Kansas		
City, sidie, zip code:								
4. Locate with "X" in section below: Sketch map:						6. Bore hole dia. 28 in Well depth 200 ft.	. Completion date	
ī (. ,		7 Cable tool Rotary		
NW NE 1					,		Bored X Reverse rotary	
						8. Use: Domestic Public supply Industry		
						_X Irrigation Air conditioning Stock		
SW SE						9. Casing: Material Me La	il field water Other	
							iNeight: Above or below.	
S						RMPPVC	Weight 31.66 lbs./ft.	
1 M	Aile					Dia. 16n. to 200. deg	•	
5. Type and color of	f material .			From	То	Dia in. to ft. dep 10. Screen: Manufacturer's		
Surface				0	3	W.A.Brown Fre	e-flo	
				3	64	Type	_ Dia. <u>16 120</u>	
Brown coleche clay				2	04	Set between 80	ft and 200 ft	
A-l med	. sand and gravel	•		64	75		'	
Sandy coleche clay				75	78		ange of material 1/2 down	
1/2 med. sand and gravel with 20 to 25% clay				78	81	11. Static water level: 92 ft. below land su	mo./day/yr.	
				81	82	12. Pumping level below lan		
Rock						195_ ft. after _2_	hrs. pumping 1100 g.p.m.	
Brown coleche clay with 35% rock				82	88	Estimated maximum yield —	hrs. pumping g.p.m.	
Fine sand				88	105	13. Water sample submitted:		
½ med. sand and gravel				105	108		Date	
						14. Well head completion: Pitless adapter	X Inches above grade	
Brown coleche clay				108		15. Well grouted? NO		
Fine sand with 30 to 35% clay mixed				129	154	With: Neat cement	Bentoni te Concrete	
A-1 med. sand and gravel				154	163	Depth: From ft. to		
				163	165	16. Nearest source of possible ft Direction		
Sandy clay				765	360	Well disinfected upon compl	etion? Yes X No	
Fine sand with 25 to 30% clay				105	109	17. Pump:	X Not installed	
A-1 coarse gravel and rock				169	187	Manufacturer's name Model number	HP Volts	
Sandy gray clay				187	192	j .	ft. capacityg.p.m.	
				192	200	Type:	Turkina	
Gray shale				772	200	Submersible Jet	Turbine Reciprocating	
(Use a second sheet if needed)				L	L	Centrifugal	Other •	
18. Elevation: 19. Remarks:					20. Water well contractor's			
2500 10' of grout and pump slab to be					This well was drilled under no is true to the best of my know	ny jurisdiction and this report wledge and belief.		
Topography: installed by the customer-he knows this					Aca-Hi Inter			
HIII					Business name Dodge	City, Kansas		
Slope is a regulation X Upland Valley Valley						Address Signal Co	1 7 0.90	
Valley Wayn (Cost						Signed Authorized re	presentative Date	