

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Meade		NW 1/4 NE 1/4 NW 1/4	11	T 32 S	R 28 EW
Distance and direction from nearest town or city street address of well if located within city?					
623 East Carthage, Meade, KS.					
2 WATER WELL OWNER: City of Meade					
RR#, St. Address, Box # : Municipal Plant 623 E. Carthage			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Meade, Ks. 67864			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 20' ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 13' ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 11.23 ft. below land surface measured on mo/day/yr 9-23-96			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 8 1/2 in. to 20' ft. and in. to ft.			
WELL WATER TO BE USED AS:					
5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Vapor Ext.					
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes No					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded X					
Blank casing diameter 2.375 in. to 10' ft. Dia in. to ft. Dia in. to SDR 13 ft.					
Casing height above land surface Flush Mt. in., weight lbs./ft. Wall thickness or gauge No. SCH 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 20' ft. to 10' ft. From ft. to ft. From ft. to ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 20' ft. to 9' ft. From ft. to ft. From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL:					
1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 9' ft. to 4' ft. From 4' ft. to 0' ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? West Southwest How many feet? 105'					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	.50	Gravel			
.50	5	Dk gray brn silty clay to clay, firm, packed, faint to no odor.			
5	13	Gray green to greenish tinted gray mottled sandy silt to sandy clay, moist to wet at 10'.			
13	18.50	Tan gray silty clay w/ dk gray banding, strong odor, soft, highly plastic, wet at 13'.			
18.50	20	Tan clayey silt, soft, wet, strong odor, highly plastic.			
Flush Mt. OK'D by Don Taylor					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-18-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 10-25-96 under the business name of JB Environmental Drilling by (signature) James Beebe					