

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Meade		NW 1/4 NE 1/4 NW 1/4		11		T 32 S		R 28 E	
Distance and direction from nearest town or city street address of well if located within city? 623 East Carthage, Meade, KS.									
2 WATER WELL OWNER: City of Meade									
RR#, St. Address, Box # : Municipal Plant 623 E. Carthage						Board of Agriculture, Division of Water Resources			
City, State, ZIP Code : Meade, Ks. 67864						Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 20' ft. ELEVATION:							
		Depth(s) Groundwater Encountered 1. 15' ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL 11.15 ft. below land surface measured on mo/day/yr 9-23-96							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield gpm; Well water was ft. after hours pumping gpm							
		Bore Hole Diameter 8 1/2" in. to 20' ft. and in. to ft.							
		WELL WATER TO BE USED AS:							
		5 Public water supply		8 Air conditioning		11 Injection well			
		1 Domestic		3 Feedlot		6 Oil field water supply		9 Dewatering	
		2 Irrigation		4 Industrial		7 Lawn and garden only		10 Monitoring well	
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted							
		Water Well Disinfected? Yes No							
5 TYPE OF BLANK CASING USED:									
1 Steel		3 RMP (SR)		5 Wrought iron		8 Concrete tile		CASING JOINTS: Glued Clamped	
2 PVC		4 ABS		6 Asbestos-Cement		9 Other (specify below)		Welded	
				7 Fiberglass				Threaded X	
Blank casing diameter 2.375 in. to 10' ft. Dia								SDR 13 ft.	
Casing height above land surface Flush Mt. in. weight								lbs./ft. Wall thickness or gauge No. SCH 40	
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel		3 Stainless steel		5 Fiberglass		8 RMP (SR)		10 Asbestos-cement	
2 Brass		4 Galvanized steel		6 Concrete tile		9 ABS		11 Other (specify)	
								12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot		3 Mill slot		5 Gauzed wrapped		8 Saw cut		11 None (open hole)	
2 Louvered shutter		4 Key punched		6 Wire wrapped		9 Drilled holes			
				7 Torch cut		10 Other (specify)			
SCREEN-PERFORATED INTERVALS:									
From 20' ft. to 10' ft.				From ft. to ft.					
From ft. to ft.				From ft. to ft.					
GRAVEL PACK INTERVALS:									
From 20' ft. to 9' ft.				From ft. to ft.					
From ft. to ft.				From ft. to ft.					
6 GROUT MATERIAL:									
1 Neat cement		3 Cement grout		3 Bentonite		4 Other			
Grout Intervals: From 9' ft. to 4' ft.		From 4' ft. to 0' ft.		From ft. to ft.		From ft. to ft.			
What is the nearest source of possible contamination:									
1 Septic tank		4 Lateral lines		7 Pit privy		10 Livestock pens		14 Abandoned water well	
2 Sewer lines		5 Cess pool		8 Sewage lagoon		11 Fuel storage		15 Oil well/Gas well	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard		12 Fertilizer storage		16 Other (specify below)	
						13 Insecticide storage			
Direction from well? Southwest						How many feet? 110'			
LITHOLOGIC LOG									
FROM	TO	LITHOLOGIC LOG						FROM	TO
0	.50	Asphalt							
.50	6	Blk-gray brn gravelly clay fill, fine-coarse grained sand, brick, concrete rubble, loose, dry, faint odor.							
6	9.50	Gray silty clay, moist to dry, faint odor, firm to soft.							
9.50	15	Gray silty clay, moist -wet at 15', soft, mod. odor.							
15	20	Tan-gray silty wet clay, sheen, strong odor, soft.							
PLUGGING INTERVALS									
Flush Mt. OK'D by Don Taylor									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-16-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 10-25-96 under the business name of JB Environmental Drilling by (signature) James Becker									