

1 LOCATION OF WATER WELL: County: Meade		Fraction NW ¼ NE ¼ SW ¼ SE ¼	Section Number 11	Township Number T 32 S	Range Number R 28 EW
Distance and direction from nearest town or city street address of well if located within city? 623 East Carthage, Meade, KS.					
2 WATER WELL OWNER: City of Meade RR#, St. Address, Box #: Municipal Plant 623 E. Carthage City, State, ZIP Code: Meade, Ks. 67864					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 27' ft. ELEVATION: ... ft. Depth(s) Groundwater Encountered 1. 14½' ft. 2. ... ft. 3. ... ft. WELL'S STATIC WATER LEVEL 10.0 ft. below land surface measured on mo/day/yr 9-23-96 Pump test data: Well water was ... ft. after ... hours pumping ... gpm Est. Yield ... gpm; Well water was ... ft. after ... hours pumping ... gpm Bore Hole Diameter 8½" in. to 27' ft., and ... in. to ... ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering ⑫ Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Product Recovery Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) <u>2 PVC</u> 4 ABS Blank casing diameter 2.375 in. to 12' ft. Dia ... in. to ... ft. Dia ... in. to SDR 13 ft. Casing height above land surface Flush Mt. in., weight ... lbs./ft. Wall thickness or gauge No. SCH 40					
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot <u>3 Mill slot</u> 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 27' ft. to 12' ft. From ... ft. to ... ft. GRAVEL PACK INTERVALS: From 27' ft. to 10' ft. From ... ft. to ... ft.					
6 GROUT MATERIAL: 1 Neat cement ② Cement grout ③ Bentonite 4 Other Grout Intervals: From 10' ft. to 4' ft. From 4' ft. to 0' ft. From ... ft. to ... ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy ⑪ Fuel storage 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below) Direction from well? South How many feet? 20'					
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					
0	.50	Asphalt			
.50	5.50	Dk brn sandy gravelly clay, dry, fraible, faint odor.			
5.50	13	Med grayish brn silty clay w/ trace amt of caliche, firm, moist to dry, slight odor.			
13	25	Blk-gray sandy silt, wet, strong odor, fine grained sand.			
25	27	Tan silty clay, firm, no odor, moist to wet, highly plastic.			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-19-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 10-25-96 under the business name of JB Environmental Drilling by (signature) James Burke					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					