

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Meade		NW 1/4 NE 1/4 NW 1/4	11	T 32 S	R 28 EW
Distance and direction from nearest town or city street address of well if located within city?					
623 East Carthage, Meade, KS.					
2 WATER WELL OWNER: City of Meade					
RR#, St. Address, Box # : Municipal Plant 623 E. Carthage			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Meade, Ks. 67864			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 20' ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 14' ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 14.02 ft. below land surface measured on mo/day/yr 9-21-96			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 8 1/2" in. to 20" ft. and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Vapor Extraction			
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped					
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded					
7 Fiberglass Threaded X					
Blank casing diameter 2.375 in. to 10' ft. Dia in. to ft. Dia in. to SDR 13 ft.					
Casing height above land surface Flush ft. in. weight lbs./ft. Wall thickness or gauge No. SCH 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)					
12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 20' ft. to 10' ft. From ft. to ft.					
From 20' ft. to 9' ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 20' ft. to 9' ft. From ft. to ft.					
From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL:					
1 Neat cement 4' 2 Cement grout 3 Bentonite 4 Other					
Grout intervals: From 9' ft. to 4' ft. From 4' ft. to 0' ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
13 Insecticide storage					
Direction from well? West Northwest How many feet? 100'					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4.50	Dk brn clay, tight, drv-moist, low plasticity.			
4.50	12.75	Tan silty clay w/ trace amt. of sand, fine grained, moist, no odor, med. plasticity.			
12.75	16.50	Grayish brn to gray clayey silt, w/ dk gray banding, mod. odor, moist-wet, soft.			
16.50	20	Gray clayey silt, moist-wet, strong odor, soft w/ fine grained sand, well rounded.			
F.H. OK'd by Don Taylor					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-21-96 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 10-25-96					
under the business name of JB Environmental Drilling by (signature) James Baker					