


1 LOCATION OF WATER WELL: County: Meade Fraction: SE 1/4 SW 1/4 SE 1/4 Section Number: 3 Township Number: T 32 S Range Number: R 28 E 10

Distance and direction from nearest town or city street address of well if located within city?
923 W. Carthage Ave., Meade, KS 67864

2 WATER WELL OWNER: Meade Cooperator & Supply
 RR#, St. Address, Box #: Randy Ackerman
 City, State, ZIP Code: P.O. Box 220 Meade, KS 67864
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 62 ft. ELEVATION: 2511.00
 Depth(s) Groundwater Encountered: 1 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL: NM ft. below land surface measured on mo/day/yr NM
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well 12 Other (Specify below)
Soil Vapor Extraction/Air Sparging
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No (No)

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded X

Blank casing diameter: 4 in. to 55 ft., Dia 2 in. to 62 ft., Dia in. to ft.
 Casing height above land surface: NM in., weight lbs./ft. Wall thickness or gauge No. Sch 40 PVC

TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-Cement
 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 11 Other (Specify)
 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 4 Mill slot 5 Guazed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 40 ft. to 55 ft., From 59.5 ft. to 62 ft.
 GRAVEL PACK INTERVALS: From 38 ft. to 62 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 1 ft. to 38 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
Last Site
 13 Insecticide storage

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.5	Concrete			
0.5	15	Silt, dry			RECEIVED
15	18	fine sand			SEP 24 2004
18	38	Sand, very fine, slightly moist, silty			BUREAU OF WATER
38	44	Sand, clean			
44	62	Silt, Caliche			
					SVE/AS1

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 07/21/04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 394 This Water Well Record was completed on (mo/day/yr) 9/14/04 under the business name of Coronado Great Plains, Inc. by (signature) Meagan E. Muir