

1 LOCATION OF WATER WELL: Fraction NW 1/4 NE 1/4 SW 1/4 Section Number 2 Township Number T 32 S Range Number 28 EW

Distance and direction from nearest town or city street address of well if located within city?  
 100' from the NE Corner of Jefferson Street & Madison Street

2 WATER WELL OWNER: Meade Cooperative Elevator & Supply  
 RR#, St. Address, Box #: North Highway 23 Board of Agriculture, Division of Water Resources  
 City, State, ZIP Code: Meade, Ks. 67864 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 2x2 grid with NW, NE, SW, SE quadrants. An 'X' is marked in the SW quadrant. A vertical scale on the left indicates 1 mile.]

4 DEPTH OF COMPLETED WELL: 55 ft. ELEVATION: NA  
 Depth(s) Groundwater Encountered 1. 43 ft. 2. ft. 3. ft.  
 WELL'S STATIC WATER LEVEL: 43.65 ft. below land surface measured on mo/day/yr 03-22-94  
 Pump test data: Well water was ft. after hours pumping gpm  
 Est. Yield gpm: Well water was ft. after hours pumping gpm  
 Bore Hole Diameter: 7 5/8 in. to 55 ft., and in. to ft.  
 WELL WATER TO BE USED AS:  
 5 Public water supply 8 Air conditioning 11 Injection well  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well  
 Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped  
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded  
 7 Fiberglass Threaded X  
 Blank casing diameter 2 in. to 35 ft., Dia in. to ft., Dia in. to ft.  
 Casing height above land surface 0 in., weight lbs./ft. Wall thickness or gauge No. sch. 40  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)  
 9 ABS 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify)  
 SCREEN-PERFORATED INTERVALS: From 55 ft. to 35 ft., From ft. to ft.  
 From ft. to ft., From ft. to ft.  
 GRAVEL PACK INTERVALS: From 55 ft. to 33 ft., From ft. to ft.  
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grout Intervals: From 0 ft. to 31 ft., From 31 ft. to 33 ft., From ft. to ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage 225  
 Direction from well? northwest How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3'	slt, med brn w/sl red tint, sl clay			
3'	6'	clay, lt oran-brn, v slty			
6	8	clay, lt oran-brn, v slty, mod amts of calic			
8	24	clay, med oran-brn, v slty, sl-mod snd-grvl szd caliche			
24	30	snd, v f-f grnd, v slty, sl-mod clay, med oran-brn			
30	35	clay, lt oran-brn, v slty, sl calic mat, sl v f-f grnd snd			
35	36	snd, v f-f grnd, sl clayey, v slty			
36	48	clay, lt-med oran-brn, mod-v lrg amts of caliche snd-grvl szd, v slty, tr v f snd			
48	55	clay, lt gry-brn, v slty, sl-mod snd, grvl szd caliche			
MW6-flush mount cover					

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 03-09-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 04-18-94 under the business name of GeoCore Services, Inc. by (signature) Dale A. Bell