		WATE	R WELL RECORD	Form WWC-5	KSA 82a-		
LOCATION OF WA		Fraction			tion Number	Township Number	Range Number
	eade		NW ¼ NE	1/4	11	T 32 S	R 28 E/W
Distance and direction	from nearest tow	vn or city street a	address of well if located	I within city?			
WATER WELL OV	VNER: Meade	e Municip	al Plant				46/
RR#, St. Address, Bo	x#: Meade	e, Ks. 67	864			Board of Agriculture,	Division of Water Resources
City, State, ZIP Code	:		with the west for the first of	Application Number:			
LOCATE WELL'S I	OCATION WITH	4 DEPTH OF C	COMPLETED WELL				
AN "X" IN SECTIO	N BOX:	Depth(s) Ground	dwater Encountered 1.		ft. 2.	$\ldots$ ft.	3
NW	NE						umping gpm umping gpm
		Bore Hole Diam	eter8in. to .		ft., a	nd	n. toft.
• w - 1	1 1	WELL WATER	TO BE USED AS:	5 Public water	r supply 8	3 Air conditioning 11	Injection well
<del>.</del>   '		1 Domestic	3 Feedlot	6 Oil field wat		Dewatering 12	
SW	SE	2 Irrigation	4 Industrial	7 Lawn and g	arden only	0 Monitoring well,	
	1 : 1 !	3		_	_		s, mo/day/yr sample was sub-
<u> </u>	<del>  '</del>	mitted	bacteriorogical campio c	0000 10 00		er Well Disinfected? Yes	No X
TYPE OF BLANK	CASING LISED:	millou	5 Wrought iron	8 Concre	· · · · · · · · · · · · · · · · · · ·		ed Clamped
		<b>7</b> \	•				•
1 Steel	3 RMP (SF	٦)	6 Asbestos-Cement		(specify below)		ded
2 PVC	4 ABS	17	7 Fiberglass				eadedX
Blank casing diamete	r <b>2</b>	.in. to !. / .	ft., Dia	in. to		ft., Dia	. in. to ft.
Casing height above	land surface	<b>0</b>	.in., weight	/ .l. Ø	Ibs./ft	. Wall thickness or gauge I	No • 1.5.4
TYPE OF SCREEN C	OR PERFORATION	N MATERIAL:		7 PV	<u>C</u>	10 Asbestos-cem	ent
1 Steel	3 Stainless	steel	5 Fiberglass	8 RM	IP (SR)	11 Other (specify	′)
2 Brass	4 Galvaniz	ed steel	6 Concrete tile	9 ABS	S	12 None used (o	pen hole)
SCREEN OR PERFO	RATION OPENIN	GS ARE:	5 Gauze	ed wrapped		8 Saw cut	11 None (open hole)
1 Continuous slot 3 Mill slot			6 Wire wrapped			9 Drilled holes	,,
2 Louvered shu		ey punched	7 Torch				
SCREEN-PERFORAT							toft.
SCHEEN-FENFORAT	ED INTERVALS.						
							toft.
GRAVEL PA	ACK INTERVALS:			<del></del>			toft.
		From	ft. to		ft., From		to ft.
GROUT MATERIA			2 Cement grout	3 Bento			
Grout Intervals: Fro	om <b>0</b>	.ft. to 3 .	ft., From	3 ft. ·	to 1.5	ft., From	ft. to ft.
What is the nearest s	ource of possible	contamination:			10 Livesto	ock pens 14	Abandoned water well
1 Septic tank 4 Lateral lines			7 Pit privy 11 Fue		11 Fuel s	torage 15	Oil well/Gas well
2 Sewer lines 5 Cess pool			8 Sewage lagoon		12 Fertilizer storage 16 Other		Other (specify below)
	wer lines 6 Seep	•	9 Feedyard		13 Insecti	cide storage Removed	Fuel Storage
Direction from well?	wer mies e eeep	ago pii	o i oodyard		How many		
FROM TO	T	LITHOLOGIC	LOG	FROM	TO		INTERVALS
	Clayey S			1			
0 6		5.T.I.C					
6   14	Silt						
1420	, –	lay					
20 27	Clayey	Sand					
				_			
		11 11 11 11					
							and an experimental section of the contract of
	<del> </del>			1			
					<del> </del>		
				+			
Z CONTRACTORIS	OD LANDOMNE	DIS CERTIFICAT	ION: This water wall	ne (1) constru	oted (2) res	setructed or (2) plugged	nder my jurisdiction and was
completed on (mo/day							nowledge and belief. Kansas
Water Well Contracto			This Water W		s completed o		7 <del>7</del> 5
under the business na		. –	A 77. 77 T			_	
			& Well, Inc		by (signatu	the correct answers. Send top three	