


1 LOCATION OF WATER WELL: Fraction SE 1/4 SW 1/4 SE 1/4 Section Number 6 Township Number T 32 S Range Number R 28 EW
 County: MEADE

Distance and direction from nearest town or city street address of well if located within city?
MEADE - 4 mi West on Hwy 54 - North -> white stucco house

2 WATER WELL OWNER: DENTON FISHER 316-873-2471
 RR#, St. Address, Box #: BOX 955 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: MEADE, KANSAS Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 280 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL 16.5 ft. below land surface measured on mo/day/yr 7-28-98
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm; Well water was ft. after hours pumping gpm
 Bore Hole Diameter 12 1/4 in. to 20 ft., and 9 1/4 in. to 280 ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes.....No. X.....; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 5.56 in. to 220 ft., Dia. in. to ft., Dia. in. to ft.
 Casing height above land surface in., weight lbs./ft. Wall thickness or gauge No.
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot .032 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 7 Torch cut 9 Drilled holes 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 220 ft. to 280 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 170 ft. to 280 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 5 ft. to 27 ft., From 165 ft. to 170 ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? South How many feet? 140

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Topsoil	195	214	Fine-med sand & Tan sandy clay streaks
3	26	Tan Clay & Caliche	214	228	Blue & Yellow Clay
26	54	Tan sandy clay & Caliche w/ Sandstone	228	244	medium sand w/ tan sandy clay streaks
54	68	med. - coarse sand	244	253	Brown, Blue, & Yellow Clay
68	86	Tan sandy clay	253	261	med. sand - small gravel
86	97	Tan clay & sandy clay	261	280	Blue Clay
97	101	Sandstone			
101	118	Coarse sand - small gravel w/ Tan sandy clay			
118	138	med - coarse sand w/ tan sandy clay			
138	149	Gravel			
149	162	Yellow Clay			
162	195	Coarse sand w/ sandy clay streaks			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-28-98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 600-A This Water Well Record was completed on (mo/day/yr) 7-28-98 under the business name of CRAMER DRIG. Co. by (signature) Ray Cramer

OFFICE USE ONLY
T
R
EW
SEC.
1/4
1/4
1/4